



# GREEN POWER GP900A-P OPEN GENSET

**Product price:**

**95.333,00 € tax excluded**

## **Product description:**

GREEN POWER GP900A-P OPEN GENSET

GREEN POWER GP900A-P OPEN is a three-phase genset with a rated of 900 kVA. It is powered by a Perkins 4006-23TAG3A engine. The genset is equipped with a MECC ALTE ECO43-2S alternator with a voltage of 400 V and a frequency of 50 Hz.

GREEN GP900A-P OPEN is designed for use in commercial and industrial applications, such as construction sites, factories and hospitals. It is ideal for providing emergency in the event of a blackout or for powering industrial machinery.

The GREEN POWER GP900A-P OPEN is a robust and reliable product that offers a number of advantages, including:

**Versatility:** the GREEN POWER GP900A-P genset can be used in a variety of applications.

**Reliability:** the GREEN POWER GP900A-P genset is robust and durable.

**Efficiency:** the genset has low consumption.

**Safety:** GREEN POWER GP900A-P genset is equipped with advanced safety systems.

## **Technical characteristics GENSET GREEN GP900A-P:**

Maximum three-phase: 900 KV

Maximum three-phase: 720 KW

Fuel: Diesel

Voltage: 230/400 V

Engine: Perkins 4006-23TAG3A

Starter: Electric

Length: 4000 mm

Width: 1800 mm





Height: 2350 mm

Weight: 6500 Kg

**You can choose between the versions:**

-Open group with AVR-Leroy alternator (automatic power pack)

-Open group with AVR-Mecc Alte alternator (automatic power pack)

-Open group with AVR-Stamford alternator (automatic power pack)

GREEN GP900A-P OPEN is a robust and reliable product that offers a number of advantages, including:

Versatility: it can be used in a variety of applications.

Reliability: it is robust and durable.

Efficiency: low consumption.

Safety: it is equipped with advanced safety systems.

If you are looking for a similar product GREEN GP900A-P or with similar features click [HERE](#).

Images purely indicative.

**Product features:**

Phase: Three phase

Maximum power three phase (KW): 720

Continuous power three phase (KW): 640

Maximum power three phase (KVA): 900

Continuous power three phase (KVA): 800

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: Perkins 4006-23TAG3A

Emissions Regulations: NON EMISSIONATO

Engine rpm (rpm): 1500

Speed governor: Electronic





Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 22921  
Number cylinders: 6  
Cylinders' position: In line  
Cooling: Water  
Alternator: LINZ PRO 22SD/4 - Sincrono  
Poles: 4  
Protection degree: IP23  
Fuel tank capacity (L): 400  
Consumption (L/h): 130 Lt/h al 75% del carico  
Running time (h): 3.07 h al 75% del carico  
Length (mm): 4000  
Width (mm): 1800  
Height (mm): 2350  
Dry weight (Kg): 6050  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR

