



---

# GREEN POWER GP1380SM/P SOUNDPROOF (MANUAL CONTROL UNIT)

**Product price:**

**185.437,00 € tax excluded**

**Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

**THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION**

**You can choose from several versions:**

- Silenced group with AVR-Leroy alternator (automatic control pack)
- Silenced group with high AVR-Mecc alternator (automatic control unit)
- Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.





**Product features:**

Phase: Three phase  
Maximum power three phase (KW): 1108  
Continuous power three phase (KW): 1002.4  
Maximum power three phase (KVA): 1385  
Continuous power three phase (KVA): 1253  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: Perkins 4012-46TWG2A  
Emissions Regulations: NON EMISSIONATO  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 45842  
Number cylinders: 12  
Cylinders' position: In line  
Cooling: Water  
Alternator: MECC ALTEECO43 2L/4  
Poles: 4  
Protection degree: IP23  
Fuel tank capacity (L): 670  
Consumption (L/h): 196 at 75% load  
Running time (h): 4.57 al 75% del carico  
Acoustic pressure: 75 dB(A)  
Length (mm): 7000  
Width (mm): 2270  
Height (mm): 2550  
Dry weight (Kg): 3630  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: AVR

