



GREEN POWER GP2500A/P OPEN (MANUAL CONTROL UNIT)

Product price:

294.952,00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 396

Continuous power three phase (KW): 480

Maximum power three phase (KVA): 495

Continuous power three phase (KVA): 600

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: 1506A-E88TAG2

Engine rpm (rpm): 1500

Speed governor: Electronic





Starting system: Electric
Engine capacity (cm³): 8800
Number cylinders: 12
Cylinders' position: In line
Cooling: Water
Alternator: LINZ PRO 22SD/4 - Sincrono
Poles: 4
Fuel tank capacity (L): 520
Consumption (L/h): 24.7 Lt/h al 75% del carico
Running time (h): 9.62 h al 75% del carico
Length (mm): 4500
Width (mm): 2050
Height (mm): 2350
Dry weight (Kg): 3430
Silenced: No
Super silenced: No
ATS Switch device : Optional
Voltage regulator: AVR