



GREEN POWER GP560S/I- N SOUNDPROOF (MANUAL CONTROL UNIT)

Product price:

49.785,00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 428

Continuous power three phase (KW): 400

Maximum power three phase (KVA): 535

Continuous power three phase (KVA): 500

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: 1506A-E88TAG2

Emissions Regulations: NON EMISSIONATO

Engine rpm (rpm): 1500





Speed governor: Electronic
Starting system: Elettrico
Engine capacity (cm³): 12880
Number cylinders: 6
Cylinders' position: In line
Cooling: Water
Alternator: MECC ALTE ECO40-3S/4
Poles: 4
Protection degree: IP23
Fuel tank capacity (L): 410
Consumption (L/h): 24.7 Lt/h al 75% del carico
Running time (h): 9.62 h al 75% del carico
Acoustic pressure: 69 dB(A)
Length (mm): 4500
Width (mm): 1450
Height (mm): 2250
Dry weight (Kg): 4430
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR