



GREEN POWER GP660A/I OPEN (MANUAL CONTROL UNIT)

Product price:

54.705,00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 528

Continuous power three phase (KW): 480

Maximum power three phase (KVA): 660

Continuous power three phase (KVA): 600

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: FPT CR16 TE1W

Emissions Regulations: NON EMISSIONATO

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Elettrico





Engine capacity (cm³): 15900
Number cylinders: 6
Cylinders' position: In line
Cooling: Water
Alternator: MECC ALTE ECO40 1.5L/4
Poles: 4
Protection degree: IP23
Fuel tank capacity (L): 340
Consumption (L/h): 84.5 Lt/h al 75% del carico
Running time (h): 4 h al 75% del carico
Length (mm): 3400
Width (mm): 1400
Height (mm): 2200
Dry weight (Kg): 350
Silenced: No
Super silenced: No
ATS Switch device : Optional
Voltage regulator: AVR

