



GREEN POWER GP700S/C SOUNDPROOF (MANUAL CONTROL UNIT)

Product price:

93.067,00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

QUESTO PRODOTTO È DISPONIBILE SOLO NELLA VERSIONE CENTRALINA AUTOMATICA

È possibile scegliere tra le versioni:

- Gruppo super silenziato con alternatore AVR-Leroy (centralina automatica)
- Gruppo super silenziato con alternatore AVR-Mecc alte (centralina automatica)
- Gruppo super silenziato con alternatore AVR-Stamford (centralina automatica)

The image is purely indicative.





Product features:

Phase: Three phase
Maximum power three phase (KW): 396
Continuous power three phase (KW): 480
Maximum power three phase (KVA): 495
Continuous power three phase (KVA): 600
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: 1506A-E88TAG2
Emissions Regulations: NON EMISSIONATO
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Elettrico
Engine capacity (cm³): 8800
Number cylinders: 6
Cylinders' position: In line
Cooling: Water
Alternator: LINZ PRO 22SD/4 - Sincrono
Poles: 4
Protection degree: IP23
Fuel tank capacity (L): 490
Consumption (L/h): 24.7 Lt/h al 75% del carico
Running time (h): 9.62 h al 75% del carico
Acoustic pressure: 69 dB(A)
Length (mm): 5000
Width (mm): 1900
Height (mm): 2350
Dry weight (Kg): 7300
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR

