



# GREEN POWER GP505S/DO-N SOUNDPROOF (MANUAL CONTROL UNIT)

**Product price:**

**44.321,00 € tax excluded**

**Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

**THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION**

**You can choose from several versions:**

- Silenced group with AVR-Leroy alternator (automatic power pack)
- Silenced group with high AVR-Mecc alternator (automatic control unit)
- Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.





**Product features:**

Phase: Three phase  
Maximum power three phase (KW): 400  
Continuous power three phase (KW): 360  
Maximum power three phase (KVA): 500  
Continuous power three phase (KVA): 450  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: 1506A-E88TAG2  
Emissions Regulations: Non Emissionati  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 14618  
Number cylinders: 8  
Cylinders' position: In line  
Cooling: Water  
Alternator: MECC ALTEECO40-2S/4  
Poles: 4  
Fuel tank capacity (L): 410  
Consumption (L/h): 24.7 Lt/h al 75% del carico  
Running time (h): 9.62 h al 75% del carico  
Acoustic pressure: 69 dB(A)  
Length (mm): 4300  
Width (mm): 1600  
Height (mm): 2300  
Dry weight (Kg): 3630  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: AVR

