



# GREEN POWER GP610A/DO-N OPEN (MANUAL CONTROL UNIT)

**Product price:**

**47.802,00 € tax excluded**

**Product description:**

GREEN POWER GP610A/DO-N OPEN (MANUAL CONTROL UNIT)

Discover the GREEN POWER GP610A/DO-N, a robust and efficient open power unit tailored for those who prefer manual control. With its user-friendly manual control unit, you can harness the power with precision and ease. Whether you're on a job site or in a remote location, this unit ensures you have reliable energy at your fingertips.

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

**Product features:**

Phase: Three phase

Maximum power three phase (KW): 484

Continuous power three phase (KW): 440

Maximum power three phase (KVA): 605





Continuous power three phase (KVA): 550  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: DOOSAN DP180LA  
Emissions Regulations: Non Emissionati  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 18273  
Number cylinders: 10  
Cylinders' position: In line  
Cooling: Water  
Alternator: MECC ALTEECO40 1L/4  
Poles: 4  
Fuel tank capacity (L): 320  
Consumption (L/h): 24.7 Lt/h al 75% del carico  
Running time (h): 9.62 h al 75% del carico  
Length (mm): 3400  
Width (mm): 1400  
Height (mm): 2100  
Dry weight (Kg): 3430  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR

