



PRAMAC LIFTER ELECTRIC STACKER GX12/25 EVO LI-ION

Product price:

6.350,00 € tax excluded

Product features:

Battery type: AGM

Drive: Electric

Operator type: Pedestrian

Load capacity (Kg): 1200

Load centre distance (mm): 600

Load axle to end forks (mm): 780

Wheel base (mm): 1234

Service weight (Kg): 570

Axle load, laden rear (Kg): 1187

Axle load, laden front (Kg): 583

Axle load, unladen front (Kg): 408

Axle load, unladen rear (Kg): 162

Tyres: front wheels: RUBBER

Tyres: stabilizers wheels: POLY.C.

Tyres: rear wheels: POLY.C.

Diameter steering wheels (mm): 250

Width steering wheels (mm): 76

Diameter load rollers (mm): 82

Width load rollers (mm): 70

Diameter stabilizers wheels front (mm): 100

Width stabilizers wheels front (mm): 38

Quantity rear wheels: 2

Quantity front wheels: 1 driven + 1

Tread front (mm): 565

Tread rear (mm): 410

Height mast lowered (mm): 1787

Lift height (mm): 2410

Height mast extended (mm): 2992

Height of tiller in drive position max (mm): 1330





Height of tiller in drive position min (mm): 960
Height lowered (mm): 90
Overall length (mm): 1760
Length to face of forks (mm): 609
Overall width (mm): 800
Thickness fork (mm): 70
Width fork (mm): 150
Length fork (mm): 1150
Fork carriage width (mm): 650
Distance between fork arms (mm): 560
Ground clearance at centre of wheelbase (mm): 20
Aisle width (mm): 2210
Turning radius (mm): 1430
Travel speed laden (Km/h): 4.7
Travel speed unladen (Km/h): 5.2
Lifting speed laden (m/s): 0.11
Lifting speed unladen (m/s): 0.19
Lowering speed laden (m/s): 0.25
Lowering speed unladen (m/s): 0.30
Max gradeability laden (%): 5
Max gradeability unladen (%): 10
Service brake: Electric
Drive motor power (KW): 0.7
Lift motor power (KW): 2.2
Battery voltage (V): 12
Battery capacity min (Ah): 110
Battery capacity max (Ah): 110
Battery weight min (Kg): 76
Battery weight max (Kg): 80
Energy consumption according to VDI cycle (KWh/h): 0.9
Sound level at driver's ear: 62
Type of lifting: Electric

