



# GENMAC Combiplus RG13000HEO-E5 GENERATOR 13,6KVA

Product price:

**2.588,00 € tax excluded**

## Product description:

GENMAC Combiplus RG13000HEO-E5 GENERATOR 13,6KVA

The **generator Genmac Combiplus RG13000HEO-E5** single phase has a Honda gasoline powered engine capable of delivering a power of 13,6KVA with the possibility of connection to optional AVR.

The GENMAC Combiplus RG13000HEO-E5 generator is equipped with a Honda Stage V engine certified for mobile use in the EU, but which does not comply with others criteria of the regulation. The engine is powered by gasoline by means of a tank with a capacity of 19 liters for an autonomy of about three and a half hours, complete with electric starter.

The Genmac 13,6KVA generator is equipped with a front control panel for portable units, with manual start and oil level sensor, with the possibility of modification by the customer with the optional remote control panel.

In combination with the generator it is possible to request the handling kit specifically designed for the selected model, for a more comfortable transport before the installation on the working lug.

The 13,6KVA generator is equipped with capacitor voltage regulator, on request it is possible to supply it with AVR voltage regulator.

## Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use





the various devices connected, improving their performance and durability.

Technical features of generator 13,6KVA Genmac Combiplus RG13000HEO-E5

Power supply: Gasoline

Firing: Electric

Phase type: Single-phase

Continuous power: 12,2KVA / 11,0KW

Maximum power: 13,6KVA / 12,2KW

Engine: Honda GX 690

Emissions regulation: Non-emissioned

Voltage: 230V

Frequency: 50 Hz

3000 rpm

Tank: 19 lt

Autonomy @ 75%: 3,4 h fixed rpm

Boosting: Manual

Length (mm): 840

Width (mm): 620

Height (mm): 690

Dry weight (Kg): 158

If you are looking for another product then you can consult on our catalog other terrestrial generators.

Images and technical data are not binding and may be subject to review

#### **Product features:**

Phase: Single phase

Maximum power single phase (KW): 12.2

Continuous power single phase (KW): 11

Maximum power single phase (KVA): 13.6

Continuous power single phase (KVA): 12.2

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Engine: Honda GX690

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric

Cooling: Air

Poles: 2





Fuel tank capacity (L): 19

Consumption (L/h): 6

Running time (h): 3.4

Length (mm): 870

Width (mm): 620

Height (mm): 690

Dry weight (Kg): 165

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Honda