



WFM KING KG160.2IV.tl.SS AUTOMATIC SILENCED GEN

Product description:

WFM KING KG160.2IV.tl.SS AUTOMATIC SILENT ELECTRONIC GROUP

KING SIZE SERIES SOUNDPROOF VERSION

STANDARD GENERATOR SET EQUIPMENT

- Steel base
- Vibration dampers
- Integrated tank with liquid collection tank
- Industrial silencer for open version
- Battery
- AUTOMATIC SWITCHBOARD ACP 6120 AMF
- Engine with original tropicalized radiator
- Emergency stop button
- Galvanized steel soundproofing cabin with residential muffler

AUTOMATIC SWITCHBOARD ACP 6120 AMF

ELECTRICAL PANEL MOUNTED ON THE GENERATOR SET WITHOUT REMOTE CONTROL

Equipment: electronic control board, circuit breaker, battery charger, square key.

Product features:

Phase: Three phase

Maximum power three phase (KW): 141





Continuous power three phase (KW): 128
Maximum power three phase (KVA): 176
Continuous power three phase (KVA): 160
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Emissions Regulations: Stage 3A
Engine rpm (rpm): 1500
Starting system: Electric
Engine capacity (cm³): 6
Number cylinders: 6
Cylinders' position: In line
Cooling: Water
Inyección : Direct
Alternator: Mecc Alte
Poles: 4
Three-phase power (KW): 128
Three-phase power (KVA): 160
Efficiency (%): 93.5
Protection degree: IP21
Bore x stroke (mm): 104 x 132
Fuel tank capacity (L): 200
Consumption (L/h): 24,8 @ 80%
Running time (h): 8
Length (mm): 3000
Width (mm): 1130
Height (mm): 1850
Dry weight (Kg): 2350
Silenced: Yes
Brushes: No
PMG: No
Product type: Generator
Type of alternator: Constant Speed
Voltage regulator: AVR
Engine manufacturer: FPT Iveco

