



VISA CK 14 GENERATOR SET SILENCED 13.1 KVA AVR

Product price:

7.425,00 € tax excluded

Product description:

GENERATOR VISA CK 14

VISA CK 14 is a silenced industrial generator set, with 13.10 KVA in continuous use and AVR, mounts top brand components: the CK 14 model uses a reliable **PERKINS diesel engine 403A-15G1** three-cylinder, 1500-rpm and a **STAMFORD PI044** alternator equipped with **AVR AS480** with 1% voltage regulation accuracy.

The **Visa CRICKET** industrial power generators feature silenced enclosures and a tropicalized treatment, making them suitable for use in hot climates; in particular the VISA CK 14 is water-cooled, which ensures excellent heat management.

The sturdy frame of the silenced generator set VISA CK 14 contains a capacious 55 liters tank, which guarantees an autonomy of more than 27 hours at 75% of load; moreover the dimensions of this genset are optimized for its transport by truck and its storage on a 40' HC container.

Main advantages of choosing a CK 14 industrial generator set:

- 1 - Original industrial diesel engine with certificate of origin
- 2 - Brushless industrial alternator with AVR
- 3 - Steel basement, tank with electro level
- 4 - Soundproofing hood completely made of galvanized sheet metal and painted with polyester powders
- 5 - Soundproofing material made of polyester fiber with high abatement
- 6 - Residential exhaust silencer with insulated collector
- 7 - Electrical panel mounted on the machine with control device and protection device integrated in the box
- 8 - Compactness for easy handling and use
- 9 - Test certification, manuals and diagrams supplied
- 10 - World wide after sales technical assistance support





11- CRICKET RANGE: FROM 9 TO 200 kVA at 50 or 60Hz.

Automatic box AMF

- 1 - On/off key;
- 2 - Emergency stop button;
- 3 - DEEP SEA® 4520 MKII;
- 4 - Main switch of primary brand.

DEEP SEA® 4520 MKII

DSE4520 panel is a compact automatic power failure control module. By monitoring a large number of motor parameters, the module is able to display warning, shutdown and motor status information on the backlit LCD display.

This control unit allows the CK 14 genset to be combined with a mains/group switching for automatic starting.

Accessories available:

- Engine pre-heating system;
- Switchboard for grid/group switching

Images and technical data are not binding

Product features:

Phase: Three phase

Maximum power three phase (KW): 11.6

Continuous power three phase (KW): 10.4

Maximum power three phase (KVA): 14.5

Continuous power three phase (KVA): 13

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: Terminal box

Engine: Perkins 403A-15G1

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 1131

Number cylinders: 3

Oil capacity (L): 4.9

Cooling: Water





Poles: 4

Three-phase power (KVA): 10

Fuel tank capacity (L): 55

Consumption (L/h): 2 at 75% of the load

Running time (h): 19.4

Length (mm): 1575

Width (mm): 745

Height (mm): 1270

Dry weight (Kg): 610

Silenced: Yes

Brushes: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Perkins

Precision of voltage regulation: $\pm 1\%$