



GENERATOR SET GP18S-PW-A - SOUNDPROOF - AUTOMATIC CONTROL PANEL

Product price:

7.965,00 € tax excluded

Product description:

The 1500 rpm generator sets are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Sturdy electrowelded steel frames with built-in variable capacity tank, engines and alternators supplied by the world's leading manufacturers in the sector and state-of-the-art control units are the elements to guarantee excellent quality generating sets.

The casings are made of steel, which allows them to be used also in tropical environments. The casings guarantee maximum accessibility for maintenance and cleaning operations.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 13.6

Continuous power three phase (KW): 12

Maximum power three phase (KVA): 17

Continuous power three phase (KVA): 15

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: Presa ausiliaria 32A 5P + Presa ausiliaria 32A 3P

Engine: PERKINS 403A-15G2

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500





Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 1496
Number cylinders: 3
Cylinders' position: In line
Cooling: Water
Alternator: Mecc Alte
Poles: 4
Fuel tank capacity (L): 70
Consumption (L/h): 3.1 at 75% of the load / 4.2 at 100% of the load
Acoustic pressure: 59 dB(A) at 7 m
Length (mm): 1750
Width (mm): 750
Height (mm): 1125
Dry weight (Kg): 590
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Precision of voltage regulation: $\pm 1\%$

