



EMILSPRAYER 30 Tank for sanitizers

Product description:

EMILSPRAYER 30 sanitizer tank

EMILSPRAYER 30 sanitizer tank perfect for spraying pesticides for agriculture and products for sanitizing and sanitizing. The EMILSPRAYER 30 sanitizer tank has a capacity of 30 litres with a flow rate of 3.8 litres/minute. The EMILSPRAYER 30 tank is small and handy as it weighs only 5 Kg. Easy to transport the EMILSPRAYER 30 hygienizer tank is suitable to be taken where you need it most.

The EMILSPRAYER 30 sanitizer tank is extremely versatile and has a wide range of applications:

- Professional cleaning and disinfection, using detergents, chemicals and germicidal liquids.
- Gardening and agriculture, in greenhouses and nurseries, using phytosanitary products, herbicides and for pest control

The EMILSPRAYER 30 tank is made of a polymer that is resistant to chemicals and UV rays; in addition, the wall thickness and the targeted design prevent deformation of the product over time and in use. The EMILSPRAYER 30 tank is equipped with a diaphragm pump with continuous duty cycle and valves made of Viton® resistant to chemicals. The integrated pressure switch activates the pump only during the product delivery phase, reducing wear and increasing efficiency. The lance ensures precise delivery by acting on the adjustable nozzle, which allows you to spray a single jet or atomise the product.

The main technical features of the EMILSPRAYER 30 tank are:

- Capacity: 30 litres
- Dimensions: 650x300xh270 mm
- Weight: 5 Kg
- Electric diaphragm pump 12V, flow rate 3.8 litres/minute, max pressure 2.8 bar
- Continuous duty cycle, Honeywell MICRO SWITCH™ pressure switch
- Santoprene™ membrane and Viton® valves resistant to chemicals
- Targeted tank design with thick walls made of chemical and UV-resistant polymer
- Aluminium lance with brass gun complete with swivel attachment. Fiberglass trigger. Range: 9 meters horizontally and 6 meters vertically.
- 4.5 meters of pipe





- Wide cap for easy filling
- Bottom drain for complete emptying of the tank
- Electrical cable and pliers for connection to the power battery and switch.

Images and technical data not binding.

Product features:

Maximum output capacity (Lt/min): 15

Pressure (bars): 2.8

Tank capacity (L): 30

Length (mm): 650

Width (mm): 300

Height (mm): 270

Dry weight (Kg): 5

Product type: Tank