



CGM 1020B HOOD WITH AUTOMATIC CONTROL UNIT

Product price:

148.713,00 € tax excluded

Product description:

These generating sets are equipped with Lombardini, Kohler, Perkins, Fpt, Fpt, Doosan, Deutz, Volvo Diesel engines, with electric starter with battery, half bell coupling and reed coupling, mounted on a fixed base, with anti-vibration mounts, fuel tank incorporated in the crankcase. Electrical panel for manual control, fixed on the group, with the following instrumentation: circuit breaker, voltmeter, 1 or 3 ammeters (depending on the power), hour meter, frequency meter, starting key, optical signal for low oil pressure, high water temperature, battery charger dynamo, minimum fuel level, with automatic stop in case of anomalies, socket or terminal board use. On request: automatic switchboards, slow or fast towing trolleys (to be registered), protective hoods, soundproof hoods, special equipment.

Images and technical data not binding.

Product features:

Phase: Three phase
Maximum power three phase (KW): 898
Continuous power three phase (KW): 816
Maximum power three phase (KVA): 1122
Continuous power three phase (KVA): 1020
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 400
Engine: PERKINS 4008 TAG2A
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric





Engine capacity (cm³): 31800
Number cylinders: 12
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 150 x 150