



MOSA GE 2000 MI

Product price:

413,00 € tax excluded

Product description:

MOSA GE2000MI supersilenced 2 KW Generator

Power generator MOSA GE2000MI, part of the portable range of MOSA, is a 2KW single-phase generator set with inverter technology voltage regulator.

The MOSA GE2000MI 2KW single-phase power generator is perfect both for hobby and professional use, thanks to the GK 80-i engine powered by gasoline and all the excellent quality components of which it is composed. The single-phase MOSA GE2000MI 2KW current generator has a manual recoil starter and a GK 80-i engine.

This single-phase MOSA GE2000MI 2KW power generator is very light, easy to transport and manoeuvre as it is compact and handy with a comfortable carrying handle.

Inverter voltage regulator

The MOSA GE2000MI 2KW single-phase power generator inverter technology regulator guarantees a constant, clean and uninterrupted power supply. In this way, thanks to the inverter technology regulator, you can connect your sensitive devices (PCs, smartphones, household appliances, etc.) to your MOSA GE2000MI 2KW power generator safely and without burning them.

Why buy this generator?

First of all, the GE2000MI 2KW power generator solves problems of power failure during blackouts in different environments, from homes to businesses. The GE2000MI 2KW power generator is also used to provide electricity on construction sites and for hobby use. Portable generators are lightweight, easy to transport, compact and robust, easy to use and with low running costs. They also have an excellent quality/price ratio.

Technical data of MOSA GE2000MI:

Maximum power Single-phase: 2 KW

Single-phase continuous use power: 1.8 KW

Fuel: Gasoline

Voltage: 230 V

Frequency: 50 Hz

Engine: GK 80-i

Starting: Manual





Consumption: 5.3 Lt/h at 75% of the load
Length: 498 mm
Width: 298 mm
Height: 459 mm
Weight: 22 Kg
Inverter
Supersilenced

If you are looking for another generator, then we recommend the generator range.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 2
Continuous power single phase (KW): 1.8
Maximum power single phase (KVA): 2
Continuous power single phase (KVA): 1.8
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A 2P+T Schuko
Engine: Yanmar 4TNV98TZ (Stage 3A)
Emissions Regulations: Stage 5
Engine rpm (rpm): 5500
Starting system: Manual
Engine capacity (cm³): 79.7
Number cylinders: 1
Oil capacity (L): 0.35
Cooling: Air
Alternator: Single-phase synchronous, self-excited, self-regulated, brushless
Bore x stroke (mm): 48.6 x 43
Fuel tank capacity (L): 5
Consumption (L/h): 5.3
Running time (h): 0.93
Acoustic power: 92 dB(A)
Acoustic pressure: 67 dB(A) at 7 m
Length (mm): 498
Width (mm): 298
Height (mm): 459
Dry weight (Kg): 20
Silenced: Yes



Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: Inverter