



---

# CGM C7000TE THREE- PHASE GENERATOR 10KVA

**Product price:**

**1.927,50 € tax excluded**

**Product description:**

CGM C7000TE Three-phase generating 7KVA

CGM C7000TE Three-phase generator of 7KVA with Honda engine powered by STAGE V gasoline at 3000 rpm, compact and easy to use, mounted on a fixed base with rubber vibration dampers. The CGM C7000TE generating set is composed of a Made in Italy alternator by Linz or NSM, self-excited with brushes and with AVR voltage regulator.

The CGM C7000TE is equipped with electric start with 12 V battery but also with manual recoil starter and with a low fuel consumption, in fact it consumes only 2 liters/hour at 75% of the load for an autonomy of up to 3 hours of operation. This CGM C7000TE is perfect for outdoor use such as for hobby use.

The CGM C7000TE generator set is part of the CLASSIC series and is easily adaptable to a variety of uses such as homes, mobile facilities, campgrounds, hobbies, construction sites etc. The CGM C7000TE generator set at 3000 rpm is suitable for emergency use only. It is not recommended to be used for more than 6 hours continuously and for more than 500 hours per year.

**Technical specifications of CGM C7000TE:**

Type of phase: Singlephase / Threephase  
Maximum singlephase power: 2.6 KVA / 2 KW  
Continuous singlephase power: 2.3 KVA / 1.8 KW  
Maximum threephase power: 7.7 KVA / 6.1 KW  
Continuous threephase power: 7 KVA / 5.6 KW  
Fuel: Petrol  
Voltage: 230/400 V  
Frequency: 50 Hz





Motor: HONDA GX390  
Motor speed: 3000 rpm  
Start: Electric  
Voltage regulator system: AVR  
Consumption: 2 Lt/h at 75% load  
Tank capacity: 6. 1 Lt  
Autonomy: 3 h at 75% load  
Length: 780 mm  
Width: 510 mm  
Height: 500 mm  
Weight: 82 Kg

Discover the full range reserved for Ground generators of CGM or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding and may be subject to change by the manufacturer.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 2  
Continuous power single phase (KW): 1.8  
Maximum power single phase (KVA): 2.6  
Continuous power single phase (KVA): 2.3  
Maximum power three phase (KW): 6.1  
Continuous power three phase (KW): 5.6  
Maximum power three phase (KVA): 7.7  
Continuous power three phase (KVA): 7  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V 16A 5P CEE - 1 x 230V 16A 3P CEE  
Engine: Honda GX390  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 389  
Number cylinders: 1  
Alternator: Made in Italy  
Poles: 2





Fuel tank capacity (L): 6.1

Consumption (L/h): 2

Running time (h): 3

Length (mm): 780

Width (mm): 510

Height (mm): 500

Dry weight (Kg): 82

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Honda

