



CGM CX7000E SINGLE- PHASE GENERATOR 7KVA

Product price:

1.950,00 € tax excluded

Product description:

GENERATOR CGM CX7000E Single-phase 7 KVA AVR

Generator CGM CX7000E single phase 7 KVA with Honda engine powered by STAGE V gasoline at 3000 rpm, compact and easy to use, mounted on a fixed base with sturdy rain cover and vibration dampers. The CGM CX7000E generator set is composed of a Made in Italy Linz or NSM alternator, self-excited without brushes and with an AVR regulator. The AVR regulator allows the voltage to be stabilized and does not ruin the connected sensitive devices. The CGM CX7000E generator set is equipped with electric start with 12V battery but also manual recoil start with recoil starter and low fuel consumption, in fact it consumes only 2 liters/hour at 75% of the load. This CGM CX7000E generator set is perfect for outdoor use such as hobby use. The CGM CX7000E generator is part of the DELUXE series and is easily adaptable to a variety of uses such as homes, mobile homes, campsites, hobbies, construction sites etc. The CGM CX7000E generator set at 3000 rpm is suitable for emergency use only. It is not recommended for use for more than 6 hours continuously and for more than 500 hours per year.

Technical specifications of CGM CX7000E generator:

Phase type: Single phase

Maximum single phase power: 6.9 KW

Maximum single phase continuous use power: 6.3 KW

Maximum single phase power: 7.7 KVA

Single-phase continuous use power: 7.7 KVA

Fuel: Gasoline

Voltage: 230 V

Frequency: 50 Hz

Engine: HONDA GX390

Engine speed: 3000 rpm

Start: Electric

Voltage regulator system: AVR

Consumption: 2 Lt/h at 75% load





Tank capacity: 6.1 Lt
Autonomy: 3 h at 75% load
Length: 825 mm
Width: 550 mm
Height: 530 mm
Weight: 91 Kg

Discover the full range reserved for generators of the best brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 6.9
Continuous power single phase (KW): 6.3
Maximum power single phase (KVA): 7.7
Continuous power single phase (KVA): 7
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A 3P CEE - 1 x 230V SCHUKO
Engine: Honda GX390
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 389
Number cylinders: 1
Alternator: Made in Italy
Poles: 2

