



CGM D6000T THREE PHASE GENERATOR 6KVA

Product price:

3.037,50 € tax excluded

Product description:

CGM D6000T Three-phase 6 KVA generator

CGM D6000T Three-phase 6 KVA generator set with Kohler engine powered by STAGE V diesel at 3000 rpm, compact and easy to use, mounted on a fixed base with rubber vibration dampers..

The CGM D6000T generator set consists of a Made in Italy alternator from Linz or NSM, self-excited with brushes and with **AVR** voltage regulator. The CGM D6000T generator set is equipped with electric start with 12V battery and with a low fuel consumption, in fact it consumes only 1,5 liters/hour at 75% of the load. This CGM D6000T is perfect for outdoor use such as hobby use.

The CGM D6000T is part of the CLASSIC DIESEL series and are characterized by lower fuel consumption and a longer life expectancy than the gasoline-powered range. The CGM D6000T at 3000 rpm is suitable for emergency use only. It is not recommended for use for more than 6 hours continuously and for more than 500 hours per year.

Technical characteristics of the CGM D6000T:

Type of phase: Singlephase / Threephase

Maximum singlephase power: 2.2 KVA / 1.8 KW

Continuous singlephase power: 2 KVA / 1.6 KW

Maximum threephase power: 6.6 KVA / 5.3 KW

Continuous threephase power: 6 KVA / 4.8 KW

Fuel: Diesel

Voltage: 230/400 V

Frequency: 50 Hz

Motor: KOHLER KD15-440

Engine rpm: 3000 rpm





Starting: Electric
Voltage regulator system: AVR
Consumption: 1.5 Lt / h at 75% of the load
Capacity tank: 4.5 Lt
Autonomy: 3 h at 75% of the load
Length: 910 mm
Width: 580 mm
Height: 640 mm
Weight: 110 Kg

Discover the full range reserved for generator of CGM or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 1.8
Continuous power single phase (KW): 1.6
Maximum power single phase (KVA): 2.2
Continuous power single phase (KVA): 2
Maximum power three phase (KW): 5.3
Continuous power three phase (KW): 4.8
Maximum power three phase (KVA): 6.6
Continuous power three phase (KVA): 6
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V 16A 5P CEE - 1 x 230V 16A 3P CEE
Engine: Kohler KD 15-440
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 442
Number cylinders: 1
Alternator: Made in Italy
Poles: 2
Fuel tank capacity (L): 4.5
Consumption (L/h): 1.5 at 75% of the load





Running time (h): 3 at 75% of the load

Length (mm): 850

Width (mm): 910

Height (mm): 640

Dry weight (Kg): 110

Voltage regulator: AVR