



CGM DS4000 SINGLE- PHASE GENERATOR 4KVA

Product price:

4.262,50 € tax excluded

Product description:

CGM DS4000 single-phase 4 KVA super-silenced generator

CGM DS4000 single-phase 4 KVA generator set with Kohler engine powered by STAGE V diesel at 3000 rpm, compact and easy to use, equipped with enclosure that lowers noise emissions and makes it **supersilenced**.

The CGM DS4000 generator is composed of a Made in Italy alternator from Linz or NSM, self-excited without brushes and with **AVR** voltage regulator.

The CGM DS4000 is equipped with electric start with 12V battery and with a low fuel consumption, in fact it consumes only 1 liter/hour at 75% of the load. This CGM DS4000 genset is perfect for outdoor use.

The CGM DS4000 genset is part of the QUIET series and are characterized by lower fuel consumption and a longer life expectancy than the gasoline-powered range and equipped with soundproof cabin suitable for installation and outdoor use, and increased fuel tank.

The CGM DS4000 3000 rpm is suitable for emergency use only. It is not recommended to be used for more than 6 hours continuously and for more than 500 hours per year.

Technical characteristics of CGM DS4000:

Phase type: Single phase

Maximum power: 3.9 KW

Continuous power: 3.6 KW

Maximum power: 4.4 KVA

Continuous power: 4 KVA

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz





Motor: KOHLER KD15-350
Engine speed: 3000 rpm
Starting: Electric
Voltage regulator system: AVR
Consumption: 1 Lt/h at 75% of the load
Tank capacity: 30 Lt
Autonomy: 30 h at 75% load
Length: 1100 mm
Width: 650 mm
Height: 900 mm
Weight: 160 Kg
Supersilenced

Discover the full range reserved for generator of CGM or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 3.9
Continuous power single phase (KW): 3.6
Maximum power single phase (KVA): 4.4
Continuous power single phase (KVA): 4
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A 3P CEE - 2 x 230V SCHUKO
Engine: Kohler KD 15-350
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 349
Number cylinders: 1
Alternator: Made in Italy
Poles: 2
Fuel tank capacity (L): 30
Consumption (L/h): 1
Running time (h): 30



Length (mm): 1100

Width (mm): 650

Height (mm): 900

Dry weight (Kg): 160

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Kohler