



DOMETIC PERFECTCHARGE MCA1225

Product price:

280,00 € tax excluded

Product description:

DOMETIC PERFECTCHARGE MCA1225 BATTERY CHARGER

DOMETIC PERFECTCHARGE MCA1225 can charge three batteries at the same time and can be used worldwide thanks to the input voltage range from 110 to 230 V. Ideal for frequent travelers around the world.

DOMETIC PERFECTCHARGE chargers guarantee 100% full charging. The unit should be fully charged at least once a month - there is no better way to take care of the cells and extend their life. Insufficient charging, on the other hand, can lead to sulfation and consequently premature aging of the battery.

DOMETIC PERFECTCHARGE MCA1225 has three outputs that allow you to charge three batteries at the same time. Charging is done very gently thanks to state-of-the-art 6-step technology. The DOMETIC PERFECTCHARGE MCA1225 has a compact and lightweight design and practical screw connections allow for quick and hassle-free mounting. With an input voltage range from 110 to 230 V, it can be used anywhere in the world and can be reliably charged even if the input voltage drops. Ideal for frequent travelers around the world. Useful improvements: remote control, battery sensor, temperature sensor or controller Dometic MPC 01 for up to 30% faster recharging.

DOMETIC PERFECTCHARGE MCA1225 BATTERY CHARGER SPECIFICATIONS

Depth: 238 mm

Height: 63 mm

Width: 179 mm

Weight: 1.7kg

Input voltage (direct current): 110/230 V

Output current: 25.00 A

Input Frequency: 50/60 Hz





Battery Type: Lead, AGM, Gel

IP Class: IP20

Energy efficiency: 87 %

Continuous power at 25: °C 225.00 W

Min. operating temperature: -20.00 °C

Max working temperature: 50.00 °C

Are you looking for a product with different characteristics? [HERE](#) you can find the entire DOMETIC range and other specialized brands.

Images and technical data are not binding and subject to change by the manufacturer.

Product features:

Frequency (Hz): 50 / 60

Battery type: Piombo, AGM, Gel

Length (mm): 283

Width (mm): 179

Height (mm): 63

Input voltage (V): 110 / 230

Product type: Battery Charger

Weight (Kg): 1.6