



MARELLIMOTORI ALTERNATOR 800KVA MJB 355 MB4

Product description:

MARELLIMOTORI MJB 355MB4 ALTERNATOR 800KVA THREE-PHASE

MARELLIMOTORI MJB 355MB4 is a three-phase alternator capable of delivering a power of **800KVA 640KW**, comes complete with AVR.

The frame of the alternator designed by MarelliMotori is equipped with side ribs to increase the resistance in addition the construction is made of strong welded steel

The 800KVA alternators MarelliMotori for continuous operation are designed to meet the vibration levels according to the standards, therefore they have a spheroidal cast iron or grey cast iron shielding.

The shaft of the MJB 355MB4 is made of carbon steel and obtained by rolling. The shaft is obtained by forging from 290 mm diameter and is tested at the manufacturer in order to verify the absence of defects.

The stator/motor core of MarelliMotori is laminated and enamelled on both sides to minimize eddy current losses

The rotor of MJB 355MB4 is of salient pole type, made with class H flat copper wire insulated with enamel coating.

The winding is held by high quality steel through rods.

All MarelliMotori are equipped with a large damping cage and are suitable for parallel operation with other generators, if equipped with the parallelization unit.

All MarelliMotori alternators can be designed to meet specific reactance values ($x'd$ and $x''d$).

The MarelliMotori alternators are all equipped with voltage regulator, in the case of the MJB 355MB4 analog. For the correct supply of voltage MARELLIMOTORI 800KVA has the need of an electronic control system, known as "voltage regulator" or "AVR" (acronym of Automatic Voltage Regulator). It guarantees the proper functioning of the machine and above all of the electrical network behind it.





The AVR is an electronic device that converts alternating current with frequency and voltage variable over time into direct current and thus avoids current surges.

The AVR designed by MarelliMotori is internally equipped with a radio noise filter, which allows to contain radio noise emitted by MarelliMotori generators within the limits set by the European regulations for industrial environments

Each engine has a type of connection to be connected to the alternator, so it is necessary to pay attention to this aspect; a model can also have from 15 to 20 different forms of construction! It is always advisable to check with the help of the technical data sheets the construction form of the desired alternator.

Select the alternator that reflects the **technical specifications you require**, visit our dedicated section to understand how.

TECHNICAL FEATURES OF THE 800KVA THREE-PHASE ALTERNATOR MJB 355MB4

Phase type: Three phase
Maximum power 50Hz: 800KVA
Maximum power 50Hz: 640KW
Maximum power 60Hz: 960KVA
Maximum power 60Hz: 768KW
Frequency: 50 - 60Hz
Voltage: 400V / 480V
Protection degree: IP23
A alternator speed: 1500 / 2250 rpm
Number of poles: 4
Yield: 96. 1%
Weight: 2050kg
Constant speed
AVR

Are you looking for a product with different characteristics? HERE you can find the entire range **MARELLIMOTORI** and other specialized brands.

Images and technical data not binding and subject to change by the manufacturer

Product features:

Phase: Single phase / Three phase
Maximum power three phase (KW): 640
Maximum power three phase (KVA): 800
Frequency (Hz): 50 / 60





Voltage (V): 400
Engine rpm (rpm): 1500
Poles: 4
Efficiency (%): 96.1
Protection degree: IP23
Brushes: No
Type of alternator: Constant Speed
Voltage regulator: AVR
Weight (Kg): 2050