



GENMAC CLICK RG5000HO GENERATOR 5,1KVA

Product price:

828,00 € tax excluded

Product description:

GENMAC CLICK RG5000HO GENERATOR 5,1KVA

The generator Genmac Click RG5000HO single phase has a Honda gasoline powered engine capable of delivering a power of 5,1KVA with the possibility of connection to optional AVR.

The Genmac Click RG5000HO single phase generator is equipped with a Honda engine powered by gasoline with a tank capacity of 5,3 liters for an autonomy of about three and a half hours, complete with manual recoil starter.

The generator is very light and makes it very easy to move for other uses, in addition for an even easier and more dynamic portability is possible the optional supply of a practical transport kit dedicated to this line of generators.

The Genmac 5,1KVA generator is portable of professional quality and you can ask for the supply with AVR.

Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

Technical features of generator 5,1KVA Genmac Click RG5000HO

Power supply: Gasoline





Single-phase

Continuous output: 4.0KW

Continuous output: 4.4KVA

Maximum output: 4,16KW

Maximum output: 5,1KVA

Voltage: 230V

Frequency: 50 Hz

3000 revolutions per minute

Tank: 5.3 Lt.

Autonomy @ 75%: 3,2 h fixed revolutions

Starting: Manual

Length (mm): 740

Width (mm): 500

Height (mm): 530

Dry weight (Kg): 59

If you are looking for another product then you can consult on our catalog other terrestrial generators.

Images and technical data are not binding and may be subject to review

Product features:

Phase: Single phase

Maximum power single phase (KW): 4.6

Continuous power single phase (KW): 4.0

Maximum power single phase (KVA): 5.1

Continuous power single phase (KVA): 4.4

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Engine: Honda GX270

Engine rpm (rpm): 3000

Starting system: Pull starter

Cooling: Air

Fuel tank capacity (L): 5.3

Running time (h): 3.2

Length (mm): 740

Width (mm): 500

Height (mm): 530

Dry weight (Kg): 59





Product type: Generator

ATS Switch device : No

Voltage regulator: AVR (optional)