



GENMAC Combiflash G221HEO-M5 THREE- PHASE MOTOR WELDER 7,2KVA

Product price:

2.231,00 € tax excluded

Product description:

GENMAC Combiflash G221HEO-M5 THREE-PHASE MOTOR WELDER 7,2KVA

The Genmac Combiflash G221HEO-M5 three-phase motor welder is equipped with a Honda GX390 Stage V Gasoline engine capable of delivering a power of 7.2KVA.

Genmac Combiflash G221HEO-M5 is ideal for having electrical power always at hand in any place and environment (construction sites, markets, beaches, camping sites or for first aid in difficult areas), combined with a powerful electrode welder.

Genmac Combiflash G221HEO-M5 is equipped with a Honda GX390 engine capable of delivering a power of 7.2KVA with gasoline supply and an "air" cooling system by means of a fan, guaranteeing maximum efficiency and durability even for long and continuous work both as a welder and as a generator set. The motorwelder generates 7.2KVA in just 3000 rpm.

The lightness of the machine and the possibility of requesting a mobilization kit are greatly appreciated by those customers who carry out repairs on streets or squares and who, due to the lack of parking space or the distance between them and their vehicles, must carry the motorwelder by hand for considerable distances (old town centers, uncomfortable areas, etc.)

On the side, the Genmac is equipped with 1 current output with 230V 16A SCHUKO type attack and 1 of the 400V 32A CEE type suitable for the connection of any electrical appliance of common use.

CHARACTERISTICS MOTOR WELDER GENMAC Combiflash G221HEO-M5 7,2KVA

Power Supply: Gasoline

Firing: Electric





Phase Type: SinglePhase / ThreePhase
Maximum SinglePhase Output: 2.4KVA / 1.9KW
Maximum ThreePhase Output: 7.2KVA / 5.7KW
Welding Current: 40 - 200 A
Maximum Welding Current: 220 A ac
Service (A): 200 - 35% / 170 - 60%
Welding Type: Electrode
Voltage: 230 / 400 V
Frequency: 50 Hz
Motor: Honda GX 390
Emission Standard: Stage V
Socket panel: 1 x Schuko 16A 230V / 1 x 32A 400 V
3000 rpm
Tank: 19 Lt.
Autonomy @ 75%: 9 h fixed rpm
Length (mm): 810
Width (mm): 550
Height (mm): 680
Dry weight (Kg): 115

If you are looking for another product then you can consult on our catalog other Motor Welders.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 1.9
Maximum power single phase (KVA): 2.4
Maximum power three phase (KW): 5.7
Maximum power three phase (KVA): 7.2
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: Honda GX390
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Cooling: Air
Poles: 2
Welding current (A): 200 - 35% / 170 - 60%
Type of welding: MMA
Current max (A): 220





Fuel tank capacity (L): 19

Running time (h): 9

Length (mm): 810

Width (mm): 550

Height (mm): 680

Dry weight (Kg): 115

Silenced: Yes

Super silenced: No

Voltage regulator: No

Engine manufacturer: Honda

