



# EGM GSC200-3-1-SE GENERATOR 5,5KW

**Product price:**

**2.150,00 € tax excluded**

## **Product description:**

### EGM GSC200-3-1-SE 5,5KW MULTIFUNCTION GENERATOR

The generator EGM GSC200-3-1-SE singlephase 5,5KW multifunction is equipped with a compression unit and a welding unit, very multipurpose and practical for every use.

Generator Singlephase EGM GSC200-3-1-SE provides reliable power for home, work and leisure environments Safe power supply of household appliances and other electronic devices Outdoor party solution.

The generator is easy to install and operate, as simple as starting and stopping with clear and intuitive controls (manual / electric / remote start) Auto power off for low oil level Durable chassis. The generator is complete with electric and remote starting control unit

The 5,5KW singlephase generator is equipped with bolted, heavy duty wheels and hinged handle to make it a robust and easy to carry. The recessed sockets with snap-on safety covers make it safer.

The multifunction generator is equipped with a control panel for the operation of welding electrodes.

The generator singlephase comes complete with a very efficient and easy-to-use compressor unit.

The generator has a practical handle with double curve, foldable to facilitate mobility and storage. The generator guarantees an efficient and silent operation thanks to the OHV motor that allows to deliver a maximum output of 5,5KW.

### TECHNICAL CHARACTERISTICS OF THE SINGLEPHASE GENERATOR GSC200-3-1-SE 5,5KW WITH AVR

Generator

Phase Type: Single Phase





Maximum Output: 5.5KW  
Continuous Output: 5KW  
Voltage: 230 V  
Frequency: 50 Hz  
DC Continuous Current: 21.7 A  
Factor: 1 cos  
Starting: Manual/Electrical  
IP Class: 21S IP  
Motor RPM: 3000 rpm  
Stationary: Fixed  
Power Supply: Gasoline  
Outputs: 1x16A/230V, 1x32A/230V

#### Welder

Work cycle: 50%  
OCV: 75 DC/V  
Current range: 50 - 200 DC/A  
Welding voltage: 22 - 28 DC/V  
Welding thickness: 1.6 - 5.0mm  
Current / Voltage rating: 180 A / 27.2 V

#### Compressor

Capacity: 0.1 m<sup>3</sup>  
Air intake: 100 l/m  
No. of stages: 1  
Pressure range: 6 - 8 bar

#### General data

Tank capacity: 230l  
Length (mm): 860  
Width (mm): 600  
Height (mm): 600  
Dry weight (Kg): 153

If you are looking for another product then you can consult other terrestrial generators in our catalog.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 5.5





Continuous power single phase (KW): 5  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Starting system: Manual / Electric  
Poles: 2  
Intake air (L/m): 100  
Pressure (bars): 6 - 8 bar  
Current range (A): 50 - 200 DC/A  
Welding voltage min/max (V): 22 - 28 DC/V  
Nominal current (A): 180 A  
Fuel tank capacity (L): 230  
Length (mm): 860  
Width (mm): 600  
Height (mm): 600  
Dry weight (Kg): 153  
Silenced: Yes  
Super silenced: No  
Rated voltage (V AC): 27,2 V  
Outputs: 1x16A/230V, 1x32A/230V

