



# EGM GSC200-4-1-SE Light Tower with Multifunctional Welder-Compressor Generator 5.5KW

**Product price:**

**3.388,35 € tax excluded**

**Product description:**

EGM GSC200-4-1-SE Light Tower with 5.5KW Multifunctional Welder-Compressor Generator

The generator GSC200-4-1-SE **singlephase** 5,5KW EGM multifunction is equipped with one compression unit and one for welding and light tower, very fertile and practical for any use.

GSC200-4-1-SE singlephase EGM generator provides reliable power for home, work and leisure environments Safe power supply of household appliances and other electronic devices solution for outdoor parties.

The generator is easy to install and operate, as simple as starting and stopping with clear and intuitive controls (manual / electric / remote start) Auto power off for low oil level Durable chassis. The generator is complete with electric and remote starting control unit

The 5,5KW singlephase generator is equipped with bolted, heavy duty wheels and hinged handle to make it a robust and easy to carry. The recessed sockets with snap-on safety covers make it safer.

The singlephase multifunction generator is equipped with a control panel for the operation of welding electrodes.

The generator is complete with a practical compressor unit and light tower for outdoor use in any condition, very efficient and easy to use.

TECHNICAL CHARACTERISTICS OF THE SINGLEPHASE GENERATOR GSC200-4-1-SE 5,5KW

Generator





Phase Type: Single Phase  
Maximum Output: 5.5KW  
Continuous Output: 5KW  
Voltage: 230 V  
Frequency: 50 Hz  
DC Continuous Current: 21.7 A  
Factor: 1 cos  
Starting: Manual/Electrical  
IP Class: 21S IP  
Motor RPM: 3000 rpm  
Stationary: Fixed  
Power Supply: Gasoline  
Outputs: 1x16A/230V, 1x32A/230V

Welder  
Duty Cycle: 50%  
OCV: 75 DC/V  
Current Range: 50 - 200 DC/A  
Welding Voltage: 22 - 28 DC/V  
Welding Thickness: 1.6 - 5.0mm  
Current / Voltage Rating: 180 A / 27.2 V

Compressor  
Capacity: 0.1 m<sup>3</sup>  
Air intake: 100 l/m  
No. of stages: 1  
Pressure range: 6 - 8 bar

Lighthouse Tower  
Lamps: 4 x 100 W LED  
Lifting height: 1800 - 4500 mm

General data  
Tank capacity: 230l  
Length (mm): 860  
Width (mm): 600  
Height (mm): 600  
Dry weight (Kg): 153

If you are looking for another product then you can consult other terrestrial generators in our catalog.

Images and technical data are not binding.





**Product features:**

Phase: Single phase

Maximum power single phase (KW): 5.5

Continuous power single phase (KW): 5

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Starting system: Manual / Electric

Poles: 2

Intake air (L/m): 100

Pressure (bars): 6 - 8 bar

Current range (A): 50 - 200 DC/A

Welding voltage min/max (V): 22 - 28 DC/V

Nominal current (A): 180 A

Fuel tank capacity (L): 230

Length (mm): 860

Width (mm): 600

Height (mm): 600

Dry weight (Kg): 153

Silenced: Yes

Super silenced: No

Outputs: 1x16A/230V, 1x32A/230V

