



GENMAC DAILY G11000KS GENERATOR 12,3KVA

Product price:

4.908,00 € tax excluded

Product description:

GENMAC DAILY G11000KS THREE-PHASE GENERATOR 12,3KVA

The generator Genmac Daily G11000KS three phase is equipped with a Kohler motor powered by diesel capable of delivering a power of 12,3KVA with capacitor voltage regulator (AVR optional).

High quality professional silenced three-phase diesel power generator, Genmac with 12,3KVA power. The Genmac diesel generator is equipped with an oversized air-cooled Kohler motor.

Genmac professional diesel generators are highly reliable machines, built with quality components to be used in professional field, where reliability is fundamental.

This feature is fundamental to guarantee a high reliability of the generator, reduces its effort and increases its life span by lowering the noise level.

All Kohler engines are built using the best materials, the most innovative techniques and the most advanced quality control methods.

Each engine is thoroughly tested to prove that it works perfectly before delivery.

In case of need, Kohler service is always at your disposal.

The 12,3KVA generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

AVR Voltage Regulator

All Genmac series models are available with optional AVR voltage regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load.

The model equipped with AVR board is highly recommended, as it guarantees a significant





improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Daily G11000KS 12,3KVA

Voltage regulator : capacitor (AVR Optional)
Power supply: Diesel
Starting: Electric
Phase type: Singlephase / Threephase
Singlephase continuous Output: 4.5KVA / 3.6KW
Maximum SinglePhase Output: 5KVA / 4KW
Continuous ThreePhase Output: 11.0KVA / 8.8KW
Maximum ThreePhase Output: 12.3KVA / 9.8KW
Motor: Kohler KD425/2
Receptacle Box: 1 x 16A 230V - 1 x 32A 230V - 1 x 16A 400V
Voltage: 230 / 400 V
Frequency: 50 Hz
3000 rpm
Tank capacity: 19 l
Autonomy @ 75%: 8 h fixed rpm
Sound pressure @7m: 72 dBa
Length (mm): 1030
Width (mm): 620
Height (mm): 804
Dry weight (Kg): 250

If you are looking for another product then you can consult other terrestrial generators in our catalog.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 4
Continuous power single phase (KW): 3.6
Maximum power single phase (KVA):
Continuous power single phase (KVA): 4.2
Maximum power three phase (KW): 9.8
Continuous power three phase (KW): 8.8
Maximum power three phase (KVA): 12.3





Continuous power three phase (KVA): 11

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 16A 230V - 1 x 32A 230V - 1 x 16A 400V

Engine: Kohler KD 425/2

Engine rpm (rpm): 3000

Starting system: Electric

Cooling: Air

Poles: 2

Fuel tank capacity (L): 19

Running time (h): 8

Acoustic pressure: 72 dB(A)

Length (mm): 1030

Width (mm): 620

Height (mm): 804

Dry weight (Kg): 250

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Kohler

