



HELVI FOX 189

Product price:

573,30 € tax excluded

Product description:

HELVI FOX189 Welding machine

HELVI FOX189 is a multi-process welding machine for MMA and MIG welding. HELVI FOX189 is a welding machine that can weld steel, stainless steel, aluminium, flux cored welding wire and brazing wire.

The main features of the HELVI FOX189 welding machine are:

- Inverter technology
- Automatically compensates for power grid imbalances
- Lightness and versatility
- Convenient patented torch and cable holder compartment
- Easy adjustment thanks to reference scales
- Excellent results even for inexperienced welders
- Suitable for use with generator

HELVI FOX189 is a single-phase welding machine with 230 V power supply and 50/60 Hz frequency. The HELVI FOX189 welding machine has a rated power of 60% of 1900 VA for a maximum current of 180.

The HELVI FOX189 welding machine is designed for MMA and MIG welding with electrodes ranging from 1,6 mm to 4 mm in diameter and for wires of different materials:

- steel (diameter from 0,6 mm to 1 mm)
- stainless steel (diameter from 0,8 mm to 1 mm)
- animated (diameter from 0,9 mm)
- aluminium (diameter from 0,8 mm to 1 mm)
- brazing (diameter from 0,8 mm to 1 mm)

The no-load voltage of the HELVI FOX189 welding machine is 54 V in MMA and 24 V in MIG.

The HELVI FOX189 welder has H insulation and IP22S protection rating.

HELVI FOX189 is very compact and comfortable to transport thanks to its light weight of about 10 Kg and the comfortable handle.

Technical characteristics of the HELVI FOX189 welding machine:





Phase type: Single-phase
Frequency: 50/60 Hz
Voltage: 230 V
Power: 1900 VA
Type of welding: Multiprocess
Open-circuit voltage: 54 V (MMA) / 24 V (MIG)
Current regulation: 20 - 180 A (MMA) / 25 - 180 A (MIG)
Duty cycle at 40°: 180 A at 20% - 75 A at 100%
Maximum current: 180 A
Steel welding wire diameter: 0.6 - 1 mm
Stainless steel welding wire diameter: 0.8 - 1 mm
Flux cored welding wire diameter: 0.9 mm
Aluminium welding wire diameter: 0.8 - 1 mm
Brazing wire diameter: 0.8 - 1 mm
Electrode diameter: 1.6 - 4 mm
Electrode type: 6013 - 7018 - CrNi
Insulation: H
Degree of protection: IP22S
Length: 480 mm
Width: 220 mm
Height: 385 mm
Weight: 10.5 Kg

If instead you are looking for another product similar to the HELVI FOX189 welding inverter, then we recommend you look at the entire range dedicated to welding machines.

Images and technical data are not binding.

Product features:

Phase: Single phase
Frequency (Hz): 50 / 60
Voltage (V): 230
Protection degree: IP22S
Power (VA): 1900
Motor insulation class: H
No-load voltage (V): 54 (MMA) / 24 (MIG)
Regulation current (A): 20 - 180 (MMA) / 25 - 180 (MIG)
Welding current (A): 180 at 20% - 75 at 100%
Diameter electrodes (mm): 1 - 4
Ø steel welding wire (mm): 0.6 - 1
Ø inox welding wire (mm): 0.8 - 1
Ø aluminium welding wire (mm): 0.8 - 1





Ø flux cored welding wire (mm): 0.9

Ø brazing wire (mm): 0.8 - 1

Type of welding: Multiprocess

Current max (A): 180

Length (mm): 480

Width (mm): 220

Height (mm): 385

Product type: Welding machine

Weight (Kg): 10.5

