



IDROMAR MC3J DUPLEX WATERMAKER 360Lt/h

Product price:

23.000,00 € tax excluded

Product description:

IDROMAR MC3J DUPLEX WATERMAKER 360Lt/h

The Watermaker IDROMAR MC3J DUPLEX consists of two reverse osmosis plants in a single frame with simultaneous or independent operation with 360Lt/h flow rate.

IDROMAR MC3J DUPLEX is an osmosis plant recommended when the user's demand for drinking water is not satisfied by a single plant.

The IDROMAR Watermaker is a reverse osmosis system with flow rate 360Lt/h very compact and effective, thanks to its modular composition it is easy to install and operate.

The IDROMAR Watermaker with 360Lt/h flow rate is incredibly accessible to facilitate the ordinary or extraordinary maintenance operations and therefore all the major works can be performed from the front panel.

It is also possible to design the unit with all built-in components such as the pre-feeding pump, sand filters and regeneration tank. The MC3J Duplex Watermaker clearly takes up more space but simplifies installation and the entire unit is compact and aesthetically pleasing.

The osmotic Watermaker units can work in either serated or simultaneous mode. The following data refers to 2 units operating simultaneously. Osmosis implantation has a number of matching accessories that improve reliability, efficiency and ease of operation and accessibility.

TECHNICAL CHARACTERISTICS HYDROMAR MC3J DUPLEX WATERMAKER 360Lt/h

Hourly production at 25°C: 360Lt/h

Daily production at 25°C: 8600 Lt/day

Salinity water produced: 300/400 PPM

Power consumption: 3 KW

Length: 800 mm

Width: 490 mm





Height: 800 mm

Weight: 220 Kg

Hydraulic connections

Sea suction: 1/2" x 2

Suction boxes: 1/2" x 2

Discharge: 3/8" x 2

Production: 3/8" x 2

If you are looking for another Watermaker similar to IDROMAR MC3J DUPLEX then we suggest you to browse our entire catalog dedicated to nautical Watermakers.

Images and technical data are not binding.

Product features:

Power (W): 3000

Length (mm): 800

Width (mm): 490

Height (mm): 800

Feed Type: 230 V

Production for hour at 25°C (Lt/h): 360

Daily production at 25°C (Lt/day): 8600

Salinity of water produced (PPM): 300/400

Capacity (Lt/h): 360

Remote panel: Digital

Weight (Kg): 220

