



HONDA Outboard BF 4AH SHNU

Product price:

1.330,00 € tax excluded

Product description:

HONDA BF6AH SHNU Outboard Engine

Honda BF6AH SHNU is an outboard motor powerful enough to take you into coastal waters on an inflatable boat or dinghy. Lightweight to carry, they include ergonomic handles and can be easily stored in the trunk of your car.

The smallest of the Honda outboards is very easy to use. Unlike 2-stroke engines, it's quiet and you don't have to worry about the mixture of oil and gasoline. So you can accelerate to the middle of a lake, up a river or cruise along the coastal strip of the sea.

The Honda BF6AH SHNU has single-cylinder 4-stroke engines with a top valve. They are easy to start with a manual system that allows the outboard to spin freely right away. Honda BF6AH outboards have the most advanced technology that precisely controls the ignition phase, so when you start it, even in cold weather, it will start without hesitation. The air-cooled BF6AH , provides great maneuverability with 360-degree rotation and an integrated fuel-saving space tank.

A centrifugal clutch allows the engine to idle without operating the propeller blades. When you want to start moving, just act on the throttle knob, the clutch engages and drives the propeller a bit like it does in an automatic transmission.

It's very important for a small boat to be nimble and able to change direction quickly. The little Honda BF6AH has a fast turning action, which is perfect for reversing without changing gears. Simply turn the rudder 180° and the boat is able to move in reverse.

Once securely mounted to the boat, you'll find that these outboards are very lightweight and easy to pull out of the water by tilting them. This way you avoid damaging your motor propellers when moving through shallow water or on shore. You can quickly get moving again by operating the spring-loaded system that allows you to lock the motor for safety.

These Honda outboards are the lightest in their class, so it's no wonder they're easy to pull out. They've been made easier to carry, with an ergonomic handle positioned at just the right balance





point, allowing you to walk normally without effort.

The sleek design has been taken care of throughout, right down to the slim gearbox that reduces drag in the water while promoting fuel economy.

The knob gives a remarkably smooth feel and is equipped with a screw-clutch that allows it to be locked at various speeds, thus relaxing your hand.

Improving the quality of our lives means, above all, taking care of the environment in which we live. We cannot allow boat fuel to pollute the marine environment. That's why Honda has made outboard engines cleaner, quieter and more environmentally friendly with the introduction of 4-stroke.

First, the aluminum housing is anodized using Honda's patented BF6AH "double seal" process (1). Then a layer of epoxy primer is applied (2) before silver gloss paint (3). As additional UV protection, a clear resin (4) is applied as a top coat. For added safety, a sacrificial anode is applied to all waterproof connectors.

Technical specifications Honda BF6AH outboard:

Net Power (kW): 4.4

Net Power (Hp): 6

Displacement: 127 cm³

Shank length: Short

Dry weight (Kg): 27.0

Starting: Manual Tear-off

Ignition System: Digital CDI

Setup and engine lift: Manual / Manual 5 positions

Transom height (mm): 434

Length (mm): 524

Width (mm): 347

Height (mm): 1200

Bore x stroke: 60×45 mm

Engine Brand: Honda

Engine Type: OHV, 4 stroke

Number of cylinders: 1

Speed of rotation at full throttle (rpm): 5,000-6,000

Cooling System: Water (with thermostat)

Are you looking for an outboard with different technical characteristics? [HERE](#) you can find the whole range Honda or other brands specializing in the field.

Images are purely indicative.





Product features:

Fuel: Gasoline

Engine: OHV, 4 stroke

Ignition: Digitale CDI

Starting system: Pull starter

Engine capacity (cm³): 127

Number cylinders: 1

Cooling: Water

Bore x stroke (mm): 60×45

Reduction ratio: 2,08

Rpm at full throttle (rpm): 5,000?6,000

Appearance and engine lifting: Manual / Manual 5 position

Transom height (mm): 434

Net power (kW): 4,4

Mechanical power (hp): 6

Fuel tank capacity (L): 1.5

Length (mm): 524

Width (mm): 347

Height (mm):

Dry weight (Kg): 27,0

Shaft Length: S