



---

# GREEN POWER GP44S-K-SV SOUNDPROOF MANUAL CONTROL PANEL

## Product description:

The 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

## Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 11.7

Maximum power single phase (KVA): 14.6

Maximum power three phase (KW): 35.2

Continuous power three phase (KW): 4

Maximum power three phase (KVA): 7.7

Continuous power three phase (KVA): 5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 63A 5P CEE - 1 x 400V 16A 5P CEE - 1 x 230V 16A 3P CEE

Engine: Kohler KDI 2504 TCR





Emissions Regulations: Stage 5  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 2482  
Number cylinders: 4  
Cooling: Water  
Alternator: Mecc Alte  
Poles: 4  
Fuel tank capacity (L): 100  
Consumption (L/h): 10  
Running time (h): 10  
Acoustic pressure: 66 dB(A) at 7 m  
Length (mm): 2260  
Width (mm): 1000  
Height (mm): 1420  
Dry weight (Kg): 950  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: AVR  
Engine manufacturer: Kohler

