



CGM PR4-160LSP

Product description:

CGM PR4-160LSP LED Light Tower with CGM petrol engine

The CGM PR4-160LSP is a simple light tower with manual lifting winch equipped with 4 floodlights capable of delivering a light output of 160W each.

CGM PR4-160LSP consists of a trolley with lockable handles with safety grip.

CGM PR4-160LSP includes CGM 6000SP SUPER POWER gasoline engine with electric start, 3000 rpm and air cooling.

CGM PR4-160LSP is equipped with a galvanized steel lifting tower capable of extending to a maximum height of 5.5 meters, including 3 feet of stabilization to secure the light tower once opened.

CGM PR4-160LSP TECHNICAL SPECIFICATIONS

Lights: 4 160W LEDs

Lit Area: 2200 Sq Ft

Max Height: 5.5 Mt

Lift: Manual

Telescopic Pole: galvanized steel

Wind stability: nr 3 stabilizers

Lumen per light: 20350 lm

Electrical power: 6 KVA / 5,4 KW

Rotation: 355 degrees

Trolley: Slow

Drives for forklift: nr 2

Power socket: 16A 230V

Voltage: 230V

Frequency: 50 Hz

Number of turns: 3000 turns/mn

Engine: 6000SP SUPER POWER CGM

Fueling: Gasoline

Type of starting: Electric





Tank capacity: 25 Lt
Autonomy with working lights: 20 hr
Engine power: 14 Hp
N. Cylinders: 1
Intake: Aspirated
Cooling: Air
Width: 1300 mm
Length: 900 mm
Height Closed: 2160 mm
Height Open: 5500 mm
Dry Weight: 280 Kg
Firing: Air
AVR

You can find many other different light towers in the section dedicated to lighting systems.

Images are purely indicative

Product features:

Phase: Single phase
Continuous power single phase (KW): 5.4
Continuous power single phase (KVA): 6
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A
Engine: 6000SP SUPER POWER CGM
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 420
Number cylinders: 1
Cooling: Air
Alternator: CGM
Poles: 2
Type of lamps: LED
Lamps: 4 x 160 W
Telescopic pole: Galvanized steel
Illuminated area (m²): 2200
Total lumens (Lm): 81400
Lifting System: Manual lifting system





Maximum height (m): 5.5

Mast rotation: 355°

Open size (mm): 1300 x 900 x 5500

Closed size (mm): 1300 x 900 x 2160

Transportability: Slow Trailer

Fuel tank capacity (L): 25

Running time (h): 20

Acoustic pressure: 70 dB(A) at 7 m

Dry weight (Kg): 280

Silenced: Yes

Engine manufacturer: CGM

