



---

# CGM PR4-160L

## Product description:

### CGM PR4-160L LED Tower Light

CGM PR4-160L is a simple light tower with manual lifting winch equipped with 4 floodlights capable of delivering a light output of 160W each.

The CGM light tower consists of a trolley with folding handles with safety grips.

CGM PR4-160L is a light tower set up to be combined with a generator of your choice between:

- 6000SP SUPER POWER, with CGM gasoline engine, AVR, 25lt tank
- CX5000 DELUXE with HONDA gasoline engine, AVR, 15lt tank
- DS4000 QUIET with KOHLER diesel engine, AVR, 30lt tank and soundproof enclosure

CGM PR4-160L is equipped with a galvanized steel lifting tower capable of extending up to 5.5 meters maximum height, including 3 feet of stabilization to secure the light tower once opened.

## CGM PR4-160L TECHNICAL FEATURES

Floodlights: 4 LED 160W

Illuminated Area: 2200 Mq

Max Height: 5.5 Mt

Lift: Manual

Telescopic pole: galvanized steel

Wind Stability: nr 3 stabilizers

Lumen per luminaire: 20350 lm

Electrical power: 5 KVA / 4.5 KW

Rotation: 355 degrees

Towing trolley: Lento

Forklift guides: nr 2

Power outlet: 16A 230V

Voltage: 230V

Frequency: 50 Hz

Width: 1300 mm

Length: 900 mm

Height Closed: 2160 mm





Height Opened: 5500 mm

Dry weight: 280 Kg

You can find many other different light towers in the section dedicated to lighting systems.

Images are purely indicative

**Product features:**

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 16A

Type of lamps: LED

Lamps: 4 x 160 W

Telescopic pole: Galvanized steel

Illuminated area (m<sup>2</sup>): 2200

Total lumens (Lm): 81400

Lifting System: Manual lifting system

Maximum height (m): 5.5

Mast rotation: 355°

Open size (mm): 1300 x 900 x 5500

Closed size (mm): 1300 x 900 x 2160

Transportability: Slow Trailer

Dry weight (Kg): 280

