



---

# CGM TP6-75L BE TOWER

## Product description:

CGM TP6-75L BE TOWER 6 X 75W

CGM TP6-75L BE TOWER is a lighting tower with manual winch lift, equipped with 6 floodlights capable of delivering a light output of 75W each.

CGM TP6-75L equipped with 6 projectors capable of delivering a light output of 160W each.

CGM TP6-75L is equipped with a galvanized steel lifting tower capable of extending up to 7 meters in maximum height, including 4 feet of stabilization to secure the light tower when opened. The lifting tower is manually operated by winch which allows maximum extension without effort.

CGM TP6-75L BE TOWER is equipped with an input plug and a 16A 230V output socket for series connection of multiple units. This allows you to connect multiple lighting units to one power source.

The CGM TP6-75L lighting tower has no generator, but it can be effectively connected with any power generator.

Images and technical data are not binding and may be subject to revision by the supplier.

## CGM TP6-75L BE TOWER TECHNICAL SPECIFICATIONS

Floodlights: 6 LED 75W

Illuminated Area: 2400 Mq

Max Height: 7 Mt

Lift: manual

Telescopic pole: galvanized steel

Wind stability: nr 4 stabilizers

Guides for forklift forks: n.6

Lumen per light: 9225 lm

Rotation: 360 degrees

Voltage: 230V





Frequency: 50 Hz  
Outlet socket: 16A 3P  
Input socket: 16A 3P  
Maximum wind resistance: 80 km/h  
Width : 930 mm  
Length: 800 mm  
Height Closed: 2300 mm  
Height Opened: 7000 mm  
Dry weight: 235 Kg

Are you looking for a product with different characteristics? Here you can find the entire range of CGM or other specialized brands.

**Product features:**

Frequency (Hz): 50  
Voltage (V): 230  
Type of lamps: LED  
Lamps: 6 x 75W  
Telescopic pole: Galvanized steel  
Illuminated area (m<sup>2</sup>): 2400  
Lifting System: Hydraulic lifting system  
Maximum height (m): 7  
Mast rotation: 360°  
Open size (mm): 930 x 800 x 7000  
Closed size (mm): 930 x 800 x 2300  
Dry weight (Kg): 235

