



MECC ALTE ECP32-2S/2 C-TYPE THREE PHASE ALTERNATOR 50 KVA AVR

Product description:

MECC ALTE ECP32-2S/2 C-TYPE THREEPHASE ALTERNATOR 50 KVA DSR

Alternator MECC ALTE ECP32-2S/2 C-TYPE threephase with a power of 50KVA, this unit has a Brushless self-exciting and self-regulating operation equipped with **DSR** voltage regulator.

The ECP32-2S/2 alternator is complete with self-regulation which is achieved through a digital electronic regulator powered by an auxiliary winding.

The MECC ALTE ECP32-2S/2 alternator is ruggedly suited to meet industry requirements and the most demanding technological specifications needed in various applications.

The ECP32-2S/2 alternator consists of a fixed stator with inclined slots and a rotating inductor. In addition, models above 15 KVA are equipped with a damping cage as standard. All alternator windings have a 2/3 pitch in order to reduce the harmonic content.

The MECC ALTE ECP32-2S/2 alternators comply with the Italian CEI 2-3 file 11111. This standard corresponds to the European EN 60034-1 and the international IEC 60034-1, is linked to the British BS 4999 Part 101, is equivalent to the German standard VDE 0530 Part 1 and is included in the French standard NF 51.111.

TECHNICAL FEATURES MECC ALTE ALTERNATOR ECP32-2S/2 C-TYPE

Phase Type: SinglePhase / ThreePhase

Maximum SinglePhase Output:

(50Hz) 33KVA / 33KW

(60Hz) 39KVA / 39KW

Continuous SinglePhase Output:

(50Hz) 29.7KVA / 29.7KW





(60Hz) 35.7KVA / 35.7KW
Maximum threephase output:
(50Hz) 50KVA / 40KW
(60Hz) 60KVA / 48KW
Continuous threephase output:
(50Hz) 45KVA / 36KW
(60Hz) 54KVA / 43. 2KW
Frequency: 50 / 60 Hz
Voltage: 230 / 400 V
Degree of protection: IP23
Alternator speed: 3000 rpm
Number of poles: 2
Efficiency: 88.1%
Width: 542.7 mm
Length: 613.5 mm
Height: 542.7 mm
Weight: 199 Kg
Constant speed alternator
Brushless
Voltage regulator: AVR

Looking for a product with different features? Here you can find the full range MECC ALTE and other specialized brands.

Images and technical data are not binding and subject to changes by the manufacturer

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 33 (50Hz) - 39 (60Hz)
Continuous power single phase (KW): 29.7 (50Hz) - 35.7 (60Hz)
Maximum power single phase (KVA): 33 (50Hz) - 39 (60Hz)
Continuous power single phase (KVA): 29.7 (50Hz) - 35.7 (60Hz)
Maximum power three phase (KW): 40 (50Hz) - 48 (60Hz)
Continuous power three phase (KW): 36 (50Hz) - 43.2 (60Hz)
Maximum power three phase (KVA): 50 (50Hz) - 60 (60Hz)
Continuous power three phase (KVA): 45 (50Hz) - 54 (60Hz)
Frequency (Hz): 50 / 60
Voltage (V): 230 / 400
Engine rpm (rpm): 3000
Poles: 2
Single-phase power (KVA): 39
Three-phase power (KVA): 60





Efficiency (%): 88.1
Protection degree: IP23
Acoustic pressure: 77 dB(A) at 7 m
Length (mm): 542.7
Width (mm): 613.5
Height (mm): 542.7
Dry weight (Kg): 199
Brushes: No
PMG: No
Type of alternator: Constant Speed
Voltage regulator: AVR
Weight (Kg): 225