



BERTOLI 15CAR44T CARDAN GENERATOR

Product description:

BERTOLI 15CAR44T PTO GENERATOR

Generator cardan Threephase BERTOLI 15CAR44T capable of delivering a power of 40 KVA with tractor connection of 1500 rpm.

The cardan generator BERTOLI 15CAR44T has a voltage of 400 V and a frequency of 50 Hz. The cardan generator BERTOLI 15CAR44T is equipped with a MECC ALTE alternator complete with AVR voltage regulator. The AVR regulator allows to stabilize the voltage and avoid damage to the connected sensitive devices.

The BERTOLI 15CAR44T generator is very reliable as it has been built and designed using high quality materials.

Gimbal generator easy to transport, install and position thanks to its compact size.

These compact gensets, robust and easy to use, are complete with a base with 3-point linkage for a secure attachment to any tractor, in addition, the model BERTOLI is equipped with standard transport trolley.

The power transmission is via the universal joint (not included), connected to the genset multiplier.

The tractor-mounted gensets are designed primarily for farms, ranches and alpine pastures, but are easily adaptable to any emergency situation.

The voltage regulator, applied to synchronous current generators, has as its objective the maintenance of a constant operation of the machine, in its regime of greater efficiency. Generally, this means to maintain the power factor at values close to 1, but if the synchronous machine is also used to phase-shift other utilities in the same settlement, these values may vary.

Technical characteristics of the generator BERTOLI 15CAR44T:

Phase type: Singlephase / Threephase

Maximum Singlephase output: 10.5 KW

Maximum SinglePhase output: 13 KVA





Maximum ThreePhase Power: 32 KW
Maximum ThreePhase Power: 40 KVA
Frequency: 50 Hz
Voltage: 400 V
Current Supplied: 63 A
Power Factor: 0.8
Motor Power: 90 HP
Motor RPM: 1500 rpm
Alternator Brand: MeccAlte
Alternator Model: Ecp32
Alternator: Self-excited brushless
Stabilization: AVR
Number of poles: 4
Mechanical protection: IP23
Length: 1100 mm
Width: 900 mm
Height: 1100 mm
Dry weight: 325 Kg

Equipment:

- Gears multiplier
- Socket panel
- 1 x 63 A 5P
- 1 x 16 A 3P
- MV and Diff Int
- Voltmeter
- Frequency Meter
- Amperometer

If you are looking for a cardan generator with different features, then we recommend that you browse our catalog of cardan generators to find the one that comes closest to your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 10.5
Maximum power single phase (KVA): 13
Maximum power three phase (KW): 32
Maximum power three phase (KVA): 40
Frequency (Hz): 50





Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 32A 5P CEE - 1 x 230V 16A 3P CEE

Engine rpm (rpm): 1500

Alternator: MECC ALTE ECP32

Poles: 4

Protection degree: IP23

Required tractor power: 90 CV

Length (mm): 1100

Width (mm): 900

Height (mm): 1100

Dry weight (Kg): 325

Silenced: No

Super silenced: No

Voltage regulator: AVR

