



AURORA TOWER LIGHT DELTA L 4X160

Product price:

6.675,00 € tax excluded

Product description:

AURORA TORRE FARO DELTA L4X160

AURORA DELTA L4X160 is a light tower with hydraulic lifting equipped with 4 floodlights capable of delivering a light output of 160W each.

AURORA DELTA L4X160 is equipped with a galvanized steel lifting tower able to extend up to 8.5 meters of maximum height, including 4 feet of stabilization to secure the light tower once opened.

AURORA DELTA L4X160 can be connected in series with other 6 modules allowing you to have a well-lit work area for any kind of intervention you have to do.

The AURORA light tower lenses feature extremely special optics designed specifically for the civil engineering and construction industries. This innovative, fully directional LED lens design ensures maximized light output and reduced waste.

The AURORA light tower's fully directional LED lens design ensures maximized light output and reduced waste.

The safety stop stops the descent at a safe height to avoid the risk of collision with the fixtures during the normal descent phase or in case of sudden failure of the telescopic ropes or the automatic brake of the lifting winch.

AURORA DELTA L4X160 is characterized by extremely compact dimensions and a squared shape that optimize and facilitate its positioning and transport on mobile means.

TECHNICAL CHARACTERISTICS AURORA DELTA L4X160

Manufacturer: Green Power

Projectors: 4 Led 160W

Lit Area: 3300 square meters





Total Lumen: 81400 lm
Max Height: 8.5 Mt
Lift: Hydraulic
Extra sockets: 1 x 16A CEE / 230 V
Pole sections: 6
Manual stabilizers: 4
Lifting hooks: 4
Max wind resistance: 110 Km/h
Fork passage guides: STD
Transportation: Stationary
Voltage: 230V
Frequency: 50 Hz
Contained tower dimensions: 980x1180x2237 mm
Open tower dimensions: 2450x2658x8500 mm
Dry weight: 550 Kg

Looking for a product with different characteristics? Here you can find the full range Green Power or other specialized brands.

The images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 16A CEE / 230 V
Starting system: Electric
Type of lamps: LED
Lamps: 4 x 160W
Telescopic pole: Galvanized steel
Illuminated area (m²): 3300
Total lumens (Lm): 81400
Lifting System: Hydraulic lifting system
Maximum height (m): 8.5
Mast rotation: 350°
Open size (mm): 2450x2658x8500
Closed size (mm): 980x1180x2237
With generator / Without generator: Without generator
Transportability: Stationary
Dry weight (Kg): 550

