



LARIUS GIOTTO k12458 AIRLESS PUMP

Product price:

2.512,30 € tax excluded

Product description:

LARIUS GIOTTO k12458 AIRLESS PUMP

LARIUS GIOTTO k12458 electric diaphragm pump, apparatus used for high-pressure spraying without the aid of air. The pump is driven by an electric motor coupled to an eccentric shaft.

The shaft acts on the hydraulic piston which, by pumping oil from the hydraulic case, sends the suction membrane into fibrillation. The movement of the membrane creates a depression. The product is sucked in, pushed towards the outlet of the pump and sent through the hose to the guns. A hydraulic valve placed at the head of the hydraulic case allows to regulate and control the pressure of the material exiting the pump.

LARIUS GIOTTO k12458 allows the spraying of liquids under high pressure, covering large surfaces with sanitizing agents, thus reducing the presence of bacteria, fungi and viruses. Through the use of the LARIUS GIOTTO, atomization is more effective, allowing the treatment of a larger surface area with less fluid consumption than other low-pressure systems.

The LARIUS GIOTTO k12458 is equipped with a trolley complete with handle that allows for convenient and easy transport.

All the components that characterize the LARIUS GIOTTO k12458 are of high quality and make it very resistant to wear and tear. This version of the LARIUS GIOTTO electric pump includes a practical tank with a maximum capacity of 50 l to contain the material to be sprayed, so that its use will be even simpler and more immediate.

TECHNICAL CHARACTERISTICS LARIUS GIOTTO k12458

Max flow rate: 8 l/m

Motor power: 2,2 Kw

Maximum pressure: 220 bar

Power supply: 110 /220/380 VAC

Frequency: 50 Hz





Sound pressure level: ? 75dB (A)

Guns: 1 Gun AT 250

Nozzle size: Up to 0.033"

Minimum motor-generator power: 5,5 Kw

Tank capacity: 50 l

Length: 1000 mm

Width: 600 mm

Height: 850 mm

Weight: 50 Kg

Are you looking for an electric pump with different features? [HERE](#) you can find the whole range LARIUS or other specialized brands

Images and technical data are not binding and may be subject to revision by the supplier

Product features:

Frequency (Hz): 50

Voltage (V): 115 / 230

Power (KW): 2.2

Maximum output capacity (Lt/min): 8

Pressure (bars): 210 Max

Tank capacity (L): 50

Length (mm): 1000

Width (mm): 600

Height (mm): 850

Dry weight (Kg): 50

Nozzle's largest diameter: 0.033"

Version: Trolley

Type of pumping group: Membrane

