



---

# VETUS GHX5SIC MARINE GENERATOR 5KVA

## Product description:

### VETUS GHX5SIC MARINE GENERATOR 5 KVA

VETUS GHX5SIC is a 5 KVA single-phase boat generator, with a 3000 rpm diesel powered, water-cooled VC1.08 engine and digital control panel.

VETUS GHX5SIC operates at a fixed number of engine revolutions, and can be placed even in small spaces thanks to their compact size. The high quality design, insulation and materials of the generators in this range ensure reliability and durability.

All VETUS GHX5SICs come with the handy digital control panel, with which the user can automatically start or shut down the generator.

The alternator of the VETUS GHX5SIC is brushless, with AVR voltage regulator, class H insulation and IP 44 protection rating of internal parts. The AVR voltage regulator avoids voltage surges and does not allow to burn sensitive electronic devices such as pc, smartphone or appliances in general.

The latest addition to the VETUS diesel generator range is based on the efficient single cylinder VC1.08 engine, therefore suitable for installation on small boats. This small but powerful generator has AVR control and is a robust worker, thanks to the electronic regulation. Due to the pure sine wave, this generator is suitable for use in combination with electronic components such as a computer. In other words, a compact and reliable companion for your boat.

The VETUS GHX5SIC thanks to its small size and modest weight is suitable to be installed on any type of boat whether for work or recreational use.

## TECHNICAL CHARACTERISTICS VETUS GHX5SIC

Maximum power Single-phase (KW): 4

Maximum power single-phase (KVA): 5

Fuel: Diesel

Voltage: 230 V





Frequency: 50 Hz  
Motor: VC1.08  
Cooling: Water  
Engine RPM: 3000 rpm  
Starting: Automatic  
Acoustic power: 65 dB (A)  
Protection class: IP 55  
Length: 770 mm  
Width: 499 mm  
Height: 544 mm  
Weight: 135 Kg

Are you looking for a generator for boats with different technical characteristics? Here you can find the whole range of VETUS or other brands specializing in this field.

Images and technical data are not binding and may be subject to revision by the supplier.

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 4  
Maximum power single phase (KVA): 5  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: VC1.08  
Emissions Regulations: Non Emissionati  
Engine rpm (rpm): 3000  
Starting system: Electric  
Cooling: Water  
Alternator: Synchronous, brushless  
Acoustic power: 65 dB (A)  
Length (mm): 770  
Width (mm): 499  
Height (mm): 544  
Dry weight (Kg): 135  
Product type: Generator  
Voltage regulator: AVR

