



NANNI QMS7.5M MARINE GENERATOR 7.5KW

Product description:

NANNI QMS7,5M MARINE GENERATOR 7.5KW

NANNI QMS7,5M is a three-phase marine generator equipped with a Kubota engine, 4 strokes with Diesel power supply capable of delivering a maximum power of 7.5KW.

The cooling system allows the NANNI QMS7,5M to work at an optimal temperature. In the case of a closed circuit heat exchanger cooling, the coolant is cooled by seawater passing through the heat exchanger. In a Keel Cooling system, engine heat is dissipated by passing coolant through pipes embedded in the hull. The NANNI QMS7,5M marine generator comes equipped with a Super Glow system for starting in cold temperatures without the risk of sudden engine failure.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS7.5M is improved, resulting in low fuel consumption.

NANNI QMS7.5M is complete with freshwater and saltwater exchanger. Also available with keel cooling system, also known as Keel Cooling. Accessible seawater pump with rubber impeller.

TECHNICAL FEATURES NANNI QMS7,5M

Phase Type: Single Phase

Maximum Power: 7.5 KW

Continuous Power: 6.6 KW

Maximum Power: 7.5 KVA

Continuous Power: 6.6 KVA

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Engine: Kubota, 3-stroke

Start: Electric

Isolation Class: H

Protection Class: IP23





Consumption: 2.5 Lt/h at full load

Length: 840 mm

Width: 489 mm

Height: 620 mm

Weight: 224 Kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase

Maximum power single phase (KW): 7.5

Continuous power single phase (KW): 6.6

Maximum power single phase (KVA): 7.5

Continuous power single phase (KVA): 6.6

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Engine: Kubota, 4 stroke

Engine rpm (rpm): 1500

Starting system: Electric

Number cylinders: 3

Cylinders' position: In line

Cooling: Water

Inyección : Indirect (E-TVCS)

Alternator: Electronic regulator

Consumption (L/h): 2.5 at 100% of the load

Length (mm): 840

Width (mm): 489

Height (mm): 620

Dry weight (Kg): 224

