



MOSA GE SX-16000 KDM

Product price:

6.430,00 € tax excluded

Product description:

MOSA GE SX-16000 KDM 14,4 KW

MOSA GE SX-16000 KDM singlephase 14,4 KW generator set with Kohler diesel engine. The MOSA GE SX-16000 KDM generator set is equipped with electric start. The alternator of the MOSA GE SX-16000 KDM generator set is synchronous and singlephase.

This MOSA is compact and convenient to maneuver and transport thanks to its compact size, its weight of 372 kg as well as the practical central hook for lifting.

The MOSA GE SX-16000 KDM generator set with 38-liter fuel tank has a fuel consumption of 3,7 liters/hour at 75% load for an autonomy of more than 10 hours.

Sockets:

1 x 230V 63A 2P+T CEE IP67

1 x 230V 32A 2P+T CEE IP67

1 x 230V 16A 2P+T CEE IP67

1 x 230V 16A 2P+T SCHUKO

Technical specifications MOSA GE SX-16000 KDM:

Maximum power Single-phase: 14.4 KW

Single-phase continuous use power: 13 KW

Maximum power Single-phase: 16 KVA

Single-phase continuous use power: 14.5 KVA

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Engine: Kohler KDW1003

Starting: Electric

Consumption: 3.7 Lt/h at 75% of the load

Length: 1784 mm

Width: 710 mm

Height: 1115 mm

Weight: 372 Kg

Supersilenced





MOSA GE SX-16000 KDM portable generator set - Kohler diesel engine electric start - Singlephase alternator

If you are looking for another product such as MOSA GE SX-16000 KDM generator set then you can browse our catalog for more terrestrial generator sets.

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 14.4

Continuous power single phase (KW): 13

Maximum power single phase (KVA): 16

Continuous power single phase (KVA): 14.5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 63A 2P+T CEE IP67 - 1 x 230V 32A 2P+T CEE IP67 - 1 x 230V 16A 2P+T CEE IP67 - 1 x 230V 16A 2P+T SCHUKO

Engine: KOHLER KDW702

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Elettrico

Alternator: Sincrono

Fuel tank capacity (L): 38

Consumption (L/h): 3..7

Running time (h): 10.5

Acoustic pressure: 62 dB(A) at 7 m

Length (mm): 1784

Width (mm): 710

Height (mm): 1115

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Kohler

