



# FISCHER PANDA 8 MINI PVMV-N/PVM-NE VEHICLE GENERATOR 7.5KW

**Product price:**

**18.628,00 € tax excluded**

## **Product description:**

FISCHER PANDA 8 MINI PVMV-N/PVM-NE VEHICLE GENERATOR 7.5KW

The generator FISCHER PANDA 8 MINI PVMV-N/PVM-NE VEHICLE GENERATOR 7.5KW single-phase is equipped with a KUBOTA Z482 engine with Diesel power supply, capable of delivering a maximum power of 7,5KW.

Veicular Generator is equipped with a silencer system completely integrated in the soundproof capsule. This solves most of the installation problems inside the vehicle, since the exhaust is already mounted.

The FISCHER PANDA generator must be installed with an external radiator. It is recommended to mount it on the roof or any other suitable location on the outside of the vehicle.

## **Equipment**

Roof radiator rd3.3 tropical 120.1.50-60

Passatetto Dia 25 mm

Set 4 vibration dampers FPB 4 x BRB 70 A40 M12 SH 40

Exhaust elbow INOX with silicone joint

Diesel filter with water softener WS180

## **TECHNICAL FEATURES FISCHER PANDA PVMV-N AGT-DC**

Single Phase Vehicular Generator

Rated Power: 7.5 kW

Continuous Power: 6.70 kW





Fuel: Diesel  
Voltage: 120 V  
Frequency: 60 Hz  
Insulation Class: H  
RPM: 3600 rpm  
Permanent Magnets  
Voltage Regulator: Capacitor  
Power Factor Cos Pi: 1. 00  
Engine KUBOTA Z482  
Cylinders: 2  
Displacement: 479 cm<sup>3</sup>  
Power: Electric 12V (24V OPTIONAL)  
Supersilenced: 52 dB(A) at 7 meters  
Type of soundproofing cover: GFK (Glass fiber reinforced polyester)  
Insulation material: 4DS  
Length: 870 mm  
Width: 580 mm  
Height: 634 mm  
Weight: 278 Kg

Are you looking for a generator with different characteristics? Here you can find the whole range of FISCHER PANDA generators or other specialized brands

Images and technical data are not binding and may be subject to revisions by the manufacturer.

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 7.5  
Continuous power single phase (KW): 6.7  
Fuel: Diesel  
Frequency (Hz): 60  
Voltage (V): 120  
Engine: KUBOTA Z482, 4 stroke  
Engine rpm (rpm): 3600  
Starting system: Electric 12 Vcc  
Engine capacity (cm<sup>3</sup>): 479  
Number cylinders: 2  
Cooling: Water  
Motor insulation class: H  
Acoustic pressure: 52 dB(A) at 7 m  
Length (mm): 870  
Width (mm): 580





Shop name

---

Height (mm): 635

Dry weight (Kg): 278

Silenced: Yes

Super silenced: Yes

PMG: Yes

Product type: Generator

Voltage regulator: Inverter

Engine manufacturer: Kubota



PrestaShop