



ITALTOWER PC750 PRO02 LIGHTING TOWER 4x320 W MULTILED WITH HOMOLOGATED TROLLEY AND GENERATOR

Product description:

ITALTOWER PC750 PRO02 LIGHT TOWER 4x320 W MULTILED WITH APPROVED TROLLEY AND GENERATOR

The ITALTOWER PC750 PRO02 Light Tower is equipped with a Kohler 15KD350 Diesel engine, capable of delivering a power of 7KW at the service of 4 LED lamps 320W.

Thanks to the 4 LED projectors ITALTOWER PC750 PRO02 can illuminate an area of 4500 square meters with a maximum luminous intensity of 166200 lm. The winch allows the manual lifting of the telescopic pole in safety thanks to an iron cable composed of 133 micro anti-twist cables improving the resistance and the capacity of the winch itself.

The ITALTOWER PC750 PRO02 is equipped with a Kohler 15KD350 Stage V engine, fully compliant with the latest European emission regulations. One of the strong points of the ITALTOWER PC750 PRO02 is undoubtedly its retractable tiller, which can be locked in a vertical position, thus facilitating the transport or storage of the tower.

ITALTOWER PC750 PRO02 has been designed in particular to simplify the operations of the Civil Protection. Practical model to install and fast to transport is indicated for applications where it is required an immediate intervention as the first aid or to illuminate an escape route.

TECHNICAL FEATURES ITALTOWER PC750 PRO02

Number of lights: 4

Lamp power: 320 W LED





Lumen: 166200 lm
Lit area: 4500 sqm
Phase type: Single phase
Maximum power: 7 KW
Sound pressure: 70dB(A) @ 7m
Voltage: 230 V
Frequency: 50 - 60 Hz
Auxiliary Power: 3 kVA
Motor: Kohler 15KD350
RPM: 3000rpm
Refrigerant: Air
Emissions Standard: Stage V
Alternator: Linz Alumen
Tank Capacity: 45 l
Fuel: Diesel
Run Time: 84 h
Maximum Height: 7.5m
Lifting System: Manual
Rotation: 355°
Wind Resistance: 110 Km/h
Trolley: Trolley approved for EU stadale use
Stabilizers 4 + 1 (wheels)
Length (mm): min 1550 - Max 2400
Width (mm): min 1425- Max 2400
Height (mm): min 2400 - Max 7500
Dry weight (Kg): 620

Are you looking for a light tower with different characteristics? Here you can find the full range of towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer

Product features:

Phase: Single phase
Maximum power single phase (KW): 7
Fuel: Diesel
Frequency (Hz): 50 / 60
Voltage (V): 230
Engine: Kohler 15KD350
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Number cylinders: 1





Cooling: Air
Alternator: Linz
Type of lamps: MULTILED
Lamps: 4 x 320 W
Telescopic pole: Vertical
Illuminated area (m²): 4500
Total lumens (Lm): 166200
Lifting System: Manual lifting system
Maximum height (m): 7.5
Mast rotation: 355°
Open size (mm): 2400 x 2400 x 7500
Length closed (mm): 1550
Width closed (mm): 1430
Height closed (mm): 2400
With generator / Without generator: With generator
Transportability: Fast Trailer
Stability to wind (Km/h): 110
Fuel tank capacity (L): 45
Running time (h): 84
Acoustic pressure: 70 dB(A) at 7 m
Engine manufacturer: Kohler
Weight (Kg): 620

