



# ITALTOWER PEGASO PRO01 LIGHTING TOWER 4x160 W MULTILED WITH HAND CART AND GENERATOR

**Product price:**

**3.778,00 € tax excluded**

**Product description:**

ITALTOWER PEGASO PRO01 LIGHTER TOWER 4x160 W MULTILED WITH HAND CART AND GENERATOR

ITALTOWER PEGASO PRO01 Light Tower is equipped with an Arion 6000 engine powered by gasoline, capable of delivering a power of 4.8KW at the service of 4 LED lamps of 160W.

The ITALTOWER PEGASO PRO01 is a compact and easy to use, with its handy trolley you can move it anywhere. Ideal for bringing light in remote areas or open countryside where there is poor lighting.

Thanks to 4 LED projectors ITALTOWER PEGASO PRO01 can illuminate an area of 2400 square meters with a maximum luminous intensity of 81400 lm. ITALTOWER PEGASO PRO01 is supplied with two retractable handles for easy transport even on uneven ground and with 3 stabilizers (2 front and 1 rear) for optimal stabilization.

## TECHNICAL FEATURES ITALTOWER PEGASO PRO01

Number of lights: 4

Lamps power: 160 W LED

Lumen: 81400 lm

Lit area: 2400 sqm

Phase type: Single phase

Maximum power: 4. 8 KW

Sound pressure: 70dB(A) @ 7m

Voltage: 230 V





Frequency: 50 Hz  
Auxiliary power supply: 3.2 kVA  
Motor: Arion 6000  
RPM: 3000rpm  
Refrigerant: Air  
Emission standard: Not Emitted  
Alternator: Arion 6000  
Tank Capacity: 25 l  
Fuel: Gasoline  
Run Time: 27 h  
Fuel Consumption: 0.9 l/h  
Maximum Height: 5.5m  
Lifting System: Manual  
Rotation: 350°  
Wind resistance: 80 Km/h  
Trolley: Hand tow  
Stabilizers: 2  
Length (mm): min 1300 - Max 1300  
Width (mm): min 560 - Max 800  
Height (mm): min 2380 - Max 5500  
Dry weight (Kg): 250

Are you looking for a light tower with different characteristics? Here you can find the full range of towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 4.8  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: Arion 6000  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 3000  
Number cylinders: 1  
Cooling: Air  
Alternator: Arion 6000  
Type of lamps: MULTILED  
Lamps: 4 x 160 W  
Telescopic pole: Vertical





Illuminated area (m<sup>2</sup>): 2400  
Total lumens (Lm): 81400  
Lifting System: Manual lifting system  
Maximum height (m): 5.5  
Mast rotation: 350°  
Open size (mm): 1300 x 800 x 5500  
Length closed (mm): 1300  
Width closed (mm): 560  
Height closed (mm): 2380  
With generator / Without generator: With generator  
Transportability: Wheels and handles  
Stability to wind (Km/h): 80 Km/h  
Fuel tank capacity (L): 25  
Consumption (L/h): 0.9  
Acoustic pressure: 70 dB(A) at 7 m  
Voltage regulator: AVR  
Weight (Kg): 250

