



TESSARI ERLE EUW500 THREE-PHASE GENERATOR 550 KVA SILENCED WITH AUTOMATIC CONTROL UNIT

Product description:

TESSARI ERLE EUW500 THREE-PHASE POWER GENERATOR 550KVA SILENCED WITH AUTOMATIC POWER STATION

TESSARI ERLE EUW500 is a three-phase generating set equipped with a BAUDOUIN 6M26G550/5 diesel engine, capable of delivering a maximum power of 550KVA, complete with AVR voltage regulator and automatic control unit.

The TESSARI ERLE EUW500 generating set is equipped with a soundproof cabin, capable of reducing the acoustic emission up to 72 dBA perceived at a distance of 7 meters. This feature allows the TESSARI ERLE EUW500 to be considered **Super Silent**

Thanks to the supplied automatic control unit, the TESSARI ERLE EUW500 can be connected to the network by means of an **ATS panel (optional)**. This allows the genset to start working instantaneously and automatically in the event of a mains power failure.

The voltage regulator included with the supply of the TESSARI ERLE EUW500, is an electronic device able to automatically regulate the voltage and eventually the frequency and/or the electric current according to set values. These values can be modified or bound to the technical characteristics of the regulator itself.

Basically, thanks to an AVR the alternating current (with frequency and voltage variable over time) coming from the alternator is regulated and transformed into direct current at constant voltage





TECHNICAL FEATURES TESSARI ERLE EUW500

Phase type: Three-phase
Continuous power: 500 kVA / 400 kW
Maximum power: 550 kVA / 440 kW
Voltage: 400V
Fuel: Diesel
Frequency: 50 Hz
RPM: 1500 rpm
Rated current: 722 A
Sound pressure at 7m. 72 dBA $\pm$ 3dB
Motor: BAUDOUIN 6M26G550/5
Voltage regulator: AVR
Tank capacity: 600 l
Consumption: 78,4 l at 75% load
Length: 5050 mm
Width: 2150 mm
Height: 2620 mm
Weight: 5460 Kg

Are you looking for a generator set with different technical characteristics? Here you can find the full range of TESSARI generator sets or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Three phase
Maximum power three phase (KW): 440
Continuous power three phase (KW): 400
Maximum power three phase (KVA): 550
Continuous power three phase (KVA): 500
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 400
Engine: BAUDOUIN 6M26G550/5
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric
Number cylinders: 6
Cooling: Coolant Liquid
Alternator: MARELLI MJB 355





Poles: 4

Protection degree: IP23

Fuel tank capacity (L): 600

Consumption (L/h): 78.4 @ 75%

Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 5050

Width (mm): 2150

Height (mm): 2620

Dry weight (Kg): 5460

Silenced: Yes

Super silenced: Yes

Brushes: No

PMG: No

Product type: Generator

ATS Switch device : Optional

Type of alternator: Constant Speed

Voltage regulator: AVR

Engine manufacturer: Baudouin

