



POWERMATE PMI3000 SINGLE PHASE GENERATOR 3KW INVERTER

Product price:

377,00 € tax excluded

Product description:

POWERMATE PMI3000 SINGLE-PHASE 3KW INVERTER GENERATOR

POWERMATE PMI3000 is a 3KW single phase generator with Pramac OHV StageV engine, gasoline powered, compact and easy to use.

The POWERMATE PMI3000 generator is equipped with an INVERTER regulated alternator, perfect for use with power tools, gardening, outdoor activities or as an emergency generator.

The POWERMATE PMI3000 single-phase generator is equipped with recoil start and has a low fuel consumption, in fact it can guarantee an autonomy of 6 hours at 50% load.

POWERMATE PMI3000 thanks to its only 38kg and a body equipped with handles and wheels, it will be extremely easy to move and use for any activity you want to assign this generator.

The POWERMATE PMI3000 single-phase generator is equipped with a frontal electric panel composed of:

Commands:

- Selector switch: O/I
- Air valve
- Pull start
- Economy mode switch (Smart throttle), automatically adjusts the engine speed according to the connected load.

STRUMENTATION:

- Voltmeter, Frequency meter and Hour meter (display)
- Available energy (indicator light - green)





- Overload and Low oil level alarms (indicator lights - red)

PROTECTIONS:

- Overload
- Low Oil Level

OUTPUTS:

- DC12V 6A

POWERMATE PMI3000 TECHNICAL FEATURES:

Phase Type: Single Phase
Maximum Power: 3.75 KVA / 3 KW
Continuous Power: 3.5 KVA / 2.8 KW
Fuel: Gasoline
Voltage: 230 V
Frequency: 50 Hz
Motor: Pramac OHV
Emission Standard: Stage V
RPM: Variable
Start: Recoil with recoil starter
Voltage regulator: Inverter
Acoustic pressure: 68 dBA @ 7 m
Tank capacity: 10 Lt
Autonomy: 6 h at 50% load
Fuel consumption: 1.6 l/h
Length: 585 mm
Width: 400 mm
Height: 450 mm
Weight: 38 Kg

Discover the full range of power generator brand POWERMATE or other top brands by browsing our catalog to find the one that best suits your technical needs.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase
Maximum power single phase (KW): 3
Continuous power single phase (KW): 2.8
Maximum power single phase (KVA): 3.75
Continuous power single phase (KVA): 3.5





Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Engine: OHV
Emissions Regulations: Stage 5
Engine rpm (rpm): Variable
Speed governor: Mechanical
Starting system: Pull starter with recoil
Cooling: Air
Fuel tank capacity (L): 10
Consumption (L/h): 1.6
Running time (h): 6 at 50% capacity
Acoustic pressure: 68 dB(A) at 7 m
Length (mm): 585
Width (mm): 400
Height (mm): 450
Dry weight (Kg): 38
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: Inverter
Video: ZgvdQu1jB6o

