



CGM 250P-C300 WITH MANUAL CONTROL PANEL

Product price:

39.563,00 € tax excluded

Product description:

CGM 250P-C300 Single/three-phase 250KVA generator super-silenced with manual control panel

The CGM 250P-C300 is a single/three phase 250KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining of soundproofing material with high noise reduction, which makes the CGM 250P-C300 super-silent. The CGM 250P-C300 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 250P-C300 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 41,5 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 250P-C300 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 250P-C300 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 220 KW / 275 KVA

Three-phase continuous power: 200 KW / 250 KVA

Maximum single-phase power: 73.33 KW / 91.67 KVA

Single-phase continuous use power: 66.67 KW / 83.33 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 1206A-E70TTAG3

Engine speed: 1500 rpm

Starting: Electric

Consumption: 41.5 Lt/h at 75% load





Length: 3700 mm
Width: 1400 mm
Height: 2250 mm
Weight: 2780 Kg
Super-silenced
AVR

If you are looking for a product like the CGM 250P-C300 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 73.33
Continuous power single phase (KW): 66.67
Maximum power single phase (KVA): 91.67
Continuous power single phase (KVA): 83.33
Maximum power three phase (KW): 220
Continuous power three phase (KW): 200
Maximum power three phase (KVA): 275
Continuous power three phase (KVA): 250
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Engine: Perkins 1206A-E70TTAG3
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric
Engine capacity (cm³): 7010
Number cylinders: 6
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 105 x 135
Fuel tank capacity (L): 250
Consumption (L/h): 41.5
Running time (h): 6





Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 3700

Width (mm): 1400

Height (mm): 2250

Dry weight (Kg): 2780

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Perkins