



CGM 280P-B300 WITH MANUAL CONTROL PANEL

Product price:

46.675,00 € tax excluded

Product description:

CGM 280P-B300 Single/three-phase 280KVA generator with manual control panel

The CGM 280P-B300 is a single/three phase 280KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This CGM 280P-B300 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 280P-B300 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 280P-B300 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 46 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 280P-B300 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 280P-B300 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 246 KW / 308 KVA

Three-phase continuous power: 224 KW / 280 KVA

Maximum single-phase power: 82 KW / 102.67 KVA

Single-phase continuous use power: 74.67 KW / 93.33 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 1506A-E88TAG4

Engine speed: 1500 rpm

Starting: Electric

Consumption: 46 Lt/h at 75% load

Length: 2800 mm

Width: 1310 mm





Height: 1800 mm
Weight: 2500 Kg
AVR

If you are looking for a product like the CGM 280P-B300 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 82
Continuous power single phase (KW): 74.67
Maximum power single phase (KVA): 102.67
Continuous power single phase (KVA): 93.33
Maximum power three phase (KW): 246
Continuous power three phase (KW): 224
Maximum power three phase (KVA): 308
Continuous power three phase (KVA): 280
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Engine: Perkins 1506A-E88TAG4
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric
Engine capacity (cm³): 8800
Number cylinders: 6
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 112 x 149
Fuel tank capacity (L): 250
Consumption (L/h): 46
Running time (h): 5.4
Length (mm): 2800
Width (mm): 1310
Height (mm): 1800





Dry weight (Kg): 2500

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Perkins