



LUXTOWER Lux M11PLUS Light Tower LED

Product price:

9.617,00 € tax excluded

Product description:

LUXTOWER LUX M11PLUS LED LIGHT TOWER

The LUXTOWER Lux M11PLUS Light Tower is the ideal solution for illuminating large areas, thanks to its advanced technology and the robustness of its components. Designed to ensure maximum energy efficiency, this light tower provides powerful and uniform illumination, making it perfect for construction sites, events, and industrial applications.

The LUXTOWER Lux M11PLUS is a compact and easily transportable light tower that can effectively illuminate areas up to 9300 sqm, with a reduced environmental impact.

Two versions available for every need:

The LUXTOWER Lux M11PLUS is available in two configurations:

Version L (Slow for Construction Sites) – Perfect for applications in enclosed spaces or with mobility restrictions.

Version V (Road Approved) – Suitable for road transport with all required safety standards.

The LUXTOWER Lux M11PLUS light tower is equipped with an 8-meter vertical telescopic mast with manual lifting and 4x320 W LED high-efficiency floodlights.

The LUXTOWER Lux M11PLUS light tower consists of a single-phase 3.5 KVA generator set powered by a Kubota Z482 diesel engine operating at 1500 rpm, enclosed in a soundproofed casing that makes it ultra-quiet.

INCLUDED WITH THE LUXTOWER Lux M11PLUS

- DSE3110 control panel
- Main / Generator selector
- Dusk sensor
- Liquid collection tank





Technical Features of LUXTOWER Lux M11PLUS Light Tower:

Projectors: 4 x 320 W LED
Illuminated Area: 9300 Sqm
Max Height: 8 m
Lifting: Manual
Engine: Kubota Z482
Maximum Single-Phase Power: 3.5 KVA
Emission Standard: STAGE V
Auxiliary Outlet: 1.3 KVA
Fuel: Diesel
Engine Speed: 1500 rpm
Max Wind Resistance: 80 km/h
Noise Level at 7 m: 65 dB (A)
Tank Capacity: 80 l
Autonomy: 145 h
Consumption: 0.55 l/h
Main / Generator Selector
Digital Control Panel DSE3110
Dusk Sensor
Liquid Collection Tank

If you are looking for other light towers like the LUXTOWER Lux M11PLUS, you can browse our full catalog dedicated to light towers from LUXTOWER or other brands.
Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KVA): 3.5
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Engine: Kubota Z482
Emissions Regulations: STAGE V
Engine rpm (rpm): 1500
Starting system: Elettrico
Number cylinders: 2
Cooling: Liquid
Alternator: Linz Synchronous or equivalent
Maximum height (m): 8
Type of lamps: LED
Lamps: 4 x 320 W
Telescopic pole: Vertical





Illuminated area (m²): 9300
Lifting System: Manual lifting system
Mast rotation: 340°
With generator / Without generator: With generator
Stability to wind (Km/h): 80 Km/h
Fuel tank capacity (L): 80
Consumption (L/h): 0.55
Running time (h): 145
Acoustic pressure: 65 dB(A) at 7 m
Silenced: Yes
Super silenced: Yes
Product type: Light tower
Engine manufacturer: Kubota
Auxiliary socket (kVA): 1.3
Dimensioni min. (mm): L : 1780 X 1380 X 2560
Dimensioni max. (mm): L : 2410 X 2520 X 8000
Peso totale a secco (Kg): L (Traino lento) : 700

