



# CGM 450F-B400 WITH AUTOMATIC CONTROL PANEL

**Product price:**

**50.388,00 € tax excluded**

## **Product description:**

CGM 450F-B400 Single/three-phase 450KVA generator with automatic control panel

The CGM 450F-B400 is a single/three phase 450KVA generator with a 1500 rpm FPT diesel engine, compact and easy to use, mounted on a fixed base. This CGM 450F-B400 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 450F-B400 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 450F-B400 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 71 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 450F-B400 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

## **Technical characteristics of the CGM 450F-B400 generator:**

Phase type: Single-phase / Three-phase

Maximum three-phase power: 396 KW / 495 KVA

Three-phase continuous power: 360 KW / 450 KVA

Maximum single-phase power: 132 KW / 165 KVA

Single-phase continuous use power: 120 KW / 150 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: FPT CURSOR13 TE6W

Engine speed: 1500 rpm

Starting: Electric

Consumption: 71 Lt/h at 75% load

Length: 2950 mm





Width: 1550 mm  
Height: 2100 mm  
Weight: 3510 Kg  
AVR

If you are looking for a product like the CGM 450F-B400 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 132  
Continuous power single phase (KW): 120  
Maximum power single phase (KVA): 165  
Continuous power single phase (KVA): 150  
Maximum power three phase (KW): 396  
Continuous power three phase (KW): 360  
Maximum power three phase (KVA): 495  
Continuous power three phase (KVA): 450  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Engine: FPT CURSOR13 TE6W  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 12880  
Number cylinders: 6  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 135 x 150  
Fuel tank capacity (L): 400  
Consumption (L/h): 71  
Running time (h): 5.6  
Width (mm): 1550  
Height (mm): 2100





Dry weight (Kg): 3510

AVR: Yes

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco